

Product data sheet

Characteristics

TSXETY4103

Ethernet TCP/IP module - 10/100 Mbit/s - web server class B30



Main

Range of product	Modicon Premium Automation platform
Product or component type	Ethernet TCP/IP module
Physical interface	RJ45 10BASE-T/100BASE-TX 1 twisted pair
Transmission rate	10/100 Mbit/s
Communication service	Uni-TE messaging SNMP agent SMTP e-mail notification Modbus TCP messaging I/O scanning Global Data FDR server Bandwidth management
Supply	Via the power supply of the rack
Local signalling	1 LED transmission/reception activity (TX/TR) 1 LED Ethernet port fault (ERR) 1 LED Ethernet network status (RUN) 1 LED collision detection (COL)

Complementary

Communication port protocol	Modbus TCP Uni-Telway
Maximum number of connections	64
Web server	Transparent ready class B30
Web feature	Data Editor (via PC terminal) Rack viewer
Marking	CE
Product compatibility	Unity Pro PL7 Pro
Current consumption	360 mA 5 V DC
Module format	Standard
Product weight	0.34 kg

Environment


Standards	CSA 1010-1 EN 61131-2 FM Class 1 Division 2 group A FM Class 1 Division 2 group B FM Class 1 Division 2 group C FM Class 1 Division 2 group D UL 508
IP degree of protection	IP20
Ambient air temperature for operation	0...60 °C
Relative humidity	10...95 % at 60 °C without condensation

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0832 - Schneider Electric declaration of conformity download declaration of conformity

Standard and Extendable Racks for Modules Mounting

Dimensions of Modules and Racks



(1) With screw terminal block modules.

(2) Maximum depth for all types of modules and their associated connectors.