



Main

Range of product	Modicon Premium Automation platform
Product or component type	Unity processor
Software designation	Unity Pro

Complementary

Number of racks	8 12 slots 16 4/6/8 slots
Number of slots	<= 128
Discrete I/O processor capacity	1024 I/O
Analogue I/O processor capacity	128 I/O
Number of application specific channel	<= 32
Number of process control channel	<= 15 up to 45 simple loops
Integrated connection type	Non isolated serial link 2 female mini DIN RS485 19.2/115 kbit/s
Communication module processor	8 3 1
Memory description	PCMCIA card 16384 kB additional data storage Internal RAM (without PCMCIA card) 192 kB program and data Internal RAM (with PCMCIA card) 192 kB data Internal RAM (with PCMCIA card) 1792 kB program
Maximum size of object areas	64 kB (elementary and derived data) unlocated internal data 64 kB (DFB and EFB function blocks) unlocated internal data 64 %MWi internal words located internal data 64 %KWi constant words located internal data 16384 %Mi located internal bits
Application structure	1 fast task 1 master task 64 event tasks
Execution time per instruction	1.75...3 µs floating points without PCMCIA card 1.75...3 µs floating points with PCMCIA card 0.32 µs word or fixed-point arithmetic with PCMCIA card 0.17 µs word or fixed-point arithmetic without PCMCIA card 0.17 µs Boolean with PCMCIA card 0.12 µs Boolean without PCMCIA card
Number of instructions per ms	6.72 Kinst/ms 100 % Boolean without PCMCIA card 5.11 Kinst/ms 65 % Boolean + 35 % fixed arithmetic without PCMCIA card 4.59 Kinst/ms 100 % Boolean with PCMCIA card 3.11 Kinst/ms 65 % Boolean + 35 % fixed arithmetic with PCMCIA card
System overhead	1 ms master task 0.35 ms fast task
Marking	CE
Local signalling	1 LED yellow activity on TER or AUX terminal port (TER) 1 LED red processor or system fault (ERR) 1 LED red I/O module or configuration fault (I/O) 1 LED green processor running (RUN)
Current consumption	1100 mA 5 V DC

Module format	Double
Product weight	0.52 kg

Environment

Standards	73/23/EEC 89/336/EEC 92/31/EEC 93/68/EEC CSA 22-2 No 142 CSA 22-2 No 213 Class I Division 2 Group A CSA 22-2 No 213 Class I Division 2 Group B CSA 22-2 No 213 Class I Division 2 Group C CSA 22-2 No 213 Class I Division 2 Group D IEC 61131-2 UL 508
Product certifications	ABS BV DNV GL LR RINA RMRS
Ambient air temperature for operation	0...60 °C
Ambient air temperature for storage	-25...70 °C
Relative humidity	5...95 % without condensation for storage 10...95 % without condensation for operation
Operating altitude	0...2000 m
Protective treatment	TC
IP degree of protection	IP20
Pollution degree	2

Standard and Extendable Racks for Modules Mounting

Dimensions of Modules and Racks



(1) With screw terminal block modules.

(2) Maximum depth for all types of modules and their associated connectors.