



Main

Range of product	Modicon Premium Automation platform
Product or component type	Double-format PL7 processor
Software designation	PL7 Junior/Pro

Complementary

Concept	Transparent Ready
Number of racks	8 12 slots 16 4/6/8 slots
Number of slots	<= 128
Discrete I/O processor capacity	1024 I/O
Analogue I/O processor capacity	128 I/O
Number of application specific channel	<= 32
Number of process control channel	<= 15 up to 45 simple loops
Integrated connection type	Non isolated serial link 2 female mini DIN 19.2/115 kbit/s Ethernet TCP/IP RJ45 10/100 Mbit/s
Communication module processor	8 AS-Interface bus modules 2 network modules 2 fieldbus modules 1 fieldbus modules (1 if CANopen used)
Memory description	PCMCIA card 384 Kwords program PCMCIA card 2688 Kwords additional data storage Internal RAM (without PCMCIA card) 64 Kwords program and data Internal RAM (with PCMCIA card) 80 Kwords data
Maximum size of object areas	32 %KWi constant words located internal data 30.5 %MWi internal words located internal data 16384 %Mi located internal bits
Application structure	1 fast task 1 master task 64 event tasks
Execution time per instruction	2.6 µs floating points with PCMCIA card 2.5 µs floating points without PCMCIA card 0.33 µs word or fixed-point arithmetic with PCMCIA card 0.17 µs word or fixed-point arithmetic without PCMCIA card 0.17 µs Boolean with PCMCIA card 0.12 µs Boolean without PCMCIA card
Number of instructions per ms	6.57 Kinst/ms 100 % Boolean without PCMCIA card 4.7 Kinst/ms 65 % Boolean + 35 % fixed arithmetic without PCMCIA card 4.49 Kinst/ms 100 % Boolean with PCMCIA card 3.08 Kinst/ms 65 % Boolean + 35 % fixed arithmetic with PCMCIA card
System overhead	1.15 ms master task 0.29 ms fast task
Marking	CE

Local signalling	1 LED yellow transmission activity (TX) 1 LED yellow reception activity (RX) 1 LED yellow Ethernet link diagnostics (STS) 1 LED yellow activity on the terminal port (TER) 1 LED red processor or system fault (ERR) 1 LED red I/O module or configuration fault (I/O) 1 LED red Ethernet TCP/IP port fault (ERR) 1 LED red collision detection (COL) 1 LED green processor running (RUN) 1 LED green Ethernet TCP/IP port ready (RUN)
Current consumption	1360 mA 5 V DC
Module format	Double

Environment


Standards	73/23/EEC 89/336/EEC 92/31/EEC 93/68/EEC CSA 22-2 No 142 CSA 22-2 No 213 Class I Division 2 Group A CSA 22-2 No 213 Class I Division 2 Group B CSA 22-2 No 213 Class I Division 2 Group C CSA 22-2 No 213 Class I Division 2 Group D IEC 61131-2 UL 508
Product certifications	ABS BV DNV GL LR RINA RMRS
Ambient air temperature for operation	0...60 °C
Ambient air temperature for storage	-25...70 °C
Relative humidity	5...95 % without condensation for storage 10...95 % without condensation for operation
Operating altitude	0...2000 m
Protective treatment	TC
IP degree of protection	IP20
Pollution degree	2

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0934 - Schneider Electric declaration of conformity download declaration of conformity

Standard and Extendable Racks for Modules Mounting

Dimensions of Modules and Racks



(1) With screw terminal block modules.

(2) Maximum depth for all types of modules and their associated connectors.