

Main

Range of product	Modicon Premium Automation platform
Product or component type	Weight indicator


Complementary

Display type	Backlit LCD
Display colour	Green
Messages display capacity	1 line of 5 characters (17.36 x 11.8 mm) minimum 2 lines of 10 characters (8.38 x 5.9 mm) for weighing applications 4 lines of 20 characters (4.34 x 2.95 mm) maximum
[Us] rated supply voltage	24 V DC non isolated
Supply	External source
Supply voltage limits	18...30 V
Residual ripple	1200 mV
Power consumption	<= 5 W
Number of key	8
Marking	CE
Height	74 mm
Width	132 mm
Depth	104 mm
Product weight	0.38 kg


Environment

Standards	CSA C22-2 No 14 EN/IEC 60068-2 EN/IEC 61131-2 UL 508
Product certifications	ATEX zone 2/22 CSA Class 1 Division 2 UL Class 1 Division 2
Ambient air temperature for operation	0...55 °C
Ambient air temperature for storage	-20...60 °C
IP degree of protection	IP65 conforming to EN/IEC 60529 IP20 rear panel conforming to EN/IEC 60529
NEMA degree of protection	NEMA 4X front panel outdoor use

Dimensions



Cut-out for Flush Mounting



Fixing by 2 spring clips (included) on 1.5...6 mm / 0.06...0.24 in. thick panel