

PRODUCT-DETAILS

TT-14-30-0-L-EU

CABLE TIE 133NT 358MM BLK NYL TWIST



General Information

Extended Product Type	TT-14-30-0-L-EU
Product ID	7TAG054780R0015
EAN	5414363925705
Catalog Description	CABLE TIE 133NT 358MM BLK NYL TWIST
Long Description	Twist Tail Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 85 Degrees Celsius (185 F), Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, Length of 358mm (14.1 Inches), Width of 4.7mm (0.186 Inch), Thickness of 1.37mm (0.054 Inch), Tensile Strength Rating of 133 Newtons (30 Pounds), Maximum Bundle Diameter 101.6mm (4.0 Inches), 50 Pack

Ordering

EAN	5414363925705
-----	---------------

Dimensions

Product Net Width	0.186 in 4.7 mm
Product Net Length	0, mm
Product Net Depth / Length	14.1 in 358 mm

Container Information

Package Level 1 Units	50 piece
Package Level 1 Width	5 in 127 mm
Package Level 1 Height	0.5 in 13 mm
Package Level 1 Depth / Length	15 in 381 mm
Package Level 2 Units	1000 piece
Package Level 2 Width	8 in 203 mm
Package Level 2 Height	6.87 in 174 mm
Package Level 2 Depth / Length	16.12 in 409 mm

Additional Information

Application	Bend again and twist motion.
Brand / Label	Catamount
Bundle Diameter	4 in 101.6 mm
Color	Black
Effective Date	20110301
Lock Type	Plastic Pawl
Material	Nylon/Polyamide 6.6
Number of Batteries	0
Product Name	PLASTIC CABLE TIE
Product Type	Twist Tail
Special Functions	Designed for quick, easy, tool-less installation. After installing, remove excess tail with a simple bend
Tensile Strength	30 lb 133 N
Thickness	0.054 in 1.37 mm
UPC	728494145907

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TT-14-30-0-L-EU
Instructions and Manuals	TT-14-30-0-L-EU

Classifications

ETIM 6	EC000046 - Cable tie
ETIM 7	EC000046 - Cable tie
UNSPSC	39121703
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5034 >> Cable ties

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Cable Ties

