



PRODUCT-DETAILS

TY175-50-100

CBL TIE 7IN NATURAL NYL 50LB



General Information

Extended Product Type	TY175-50-100
Product ID	7TAG054360R0157
EAN	5414363075158
Catalog Description	CBL TIE 7IN NATURAL NYL 50LB
Long Description	Cable Tie, Natural Polyamide (Nylon 6.6) for Temperatures up to 85 Degrees Celsius (185 F) for Indoor Applications, UL/EN/CSA62275 Type 2/21S Rated for AH-2 Plenum and as a Flexible Cable and Conduit Support, Length of 186.43mm (7.34 Inches), Width of 4.674mm (0.184 Inches), Thickness of 1.24mm (0.049 Inches), Tensile Strength Rating of 220 Newtons (50 Pounds), 100 Pack

Ordering

EAN	5414363075158
-----	---------------

Dimensions

Product Net Width	0.184 in 4.674 mm
Product Net Length	0, mm
Product Net Depth / Length	7.34 in 186.43 mm

Container Information

Package Level 1 Units	100 piece
Package Level 1 Width	13.1 in 333 mm
Package Level 1 Height	9.1 in 231 mm
Package Level 1 Depth / Length	20.7 in 526 mm
Package Level 2 Units	1000 piece
Package Level 2 Width	9.25 in 235 mm
Package Level 2 Height	4.75 in 121 mm
Package Level 2 Depth / Length	9.5 in 241 mm

Additional Information

Brand / Label	Catamount
Bundle Diameter	0.06 to 1.73 in 1.6 to 44 mm
Color	Natural
Effective Date	19930630
Lock Type	Plastic Pawl
Material	Nylon/Polyamide 6.6
Number of Batteries	0
Product Name	PLASTIC CABLE TIE
Product Type	General Purpose
Special Functions	The integrally formed nylon pawl combines low insertion and high locking strength.
Standards	UL E49405
Tensile Strength	50 lb 220 N
Thickness	0.049 in 1.24 mm
UPC	786210918068

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TY175-50-100
Declaration of Conformity - CE	9AKK107492A9843
Instructions and Manuals	TY175-50-100

Classifications

ETIM 6	EC000046 - Cable tie
ETIM 7	EC000046 - Cable tie
UNSPSC	39121703
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5034 >> Cable ties

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Cable Ties

