

203.2 mm

.001 lb .454 g

PRODUCT-DETAILS

## **TY232MX-RW**TY232MX FOR RAILWAY

| General Information   |  |
|-----------------------|--|
| Extended Product Type | TY232MX-RW   |
| Product ID            | 7TCG009040R0014  |
| EAN                   | 5415022170177  |
| Catalog Description   | TY232MX FOR RAILWAY  |
| Long Description      | Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 105 Degrees Celsius (221 F), Weather and Ultraviolet Resistant for Exterior Applications, Length of 203.2mm (8.0 Inches), Width of 2.54mm (0.10 Inches), Thickness of 1.10mm (0.05 Inches), Tensile  Strength Rating of 80 Newtons (18 Pounds), 1000 Bulk Pack |
| Ordering              |  |
| EAN                   | 5415022170177  |
|                       |  |
| Dimensions            |  |
| Product Net Width     | 0.09 in<br>2.29 mm   |
| Product Net Depth /   |  |

## **Container Information**

Length

Product Net Weight

| Package Level 1 Units   | 1000 piece  |
|-------------------------|-------------|
| Package Level 1 Width   | 11 in       |
|                         | 279 mm      |
| Package Level 1 Height  | 1.17 in     |
|                         | 30 mm       |
| Package Level 1 Depth / | 11.39 in    |
| Length                  | 289 mm      |
| Package Level 2 Units   | 10000 piece |
| Package Level 2 Width   | 10.61 in    |
|                         | 269 mm      |
| Package Level 2 Height  | 9.03 in     |
|                         | 229 mm      |
| Package Level 2 Depth / | 14.14 in    |
| Length                  | 359 mm      |

| Additional Information |  |
|------------------------|--|
| Brand / Label          | Ty-Rap   |
| Bundle Diameter        | 2 in   |
|                        | 50.8 mm  |
| Color                  | Black  |
| Material               | Nylon/Polyamide 6.6  |
| Number of Batteries    | 0  |
| Product Name           | OTHER ARTICLES OF PLASTIC  |
| Product Type           | Railway  |
| Special Functions      | Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time. |
| Standards              | UL E49405  |
| Tensile Strength       | 18 lb<br>80 N  |
| UPC                    | 786209672001   |

| Certificates and Declarations (Document Number) |                 |  |
|---|-----------------|--|
| Data Sheet, Technical<br>Information            | TY232MX-RW      |  |
| Declaration of<br>Conformity - CE               | 9AKK107492A9841 |  |
| Instructions and<br>Manuals                     | TY232MX-RW      |  |

| Classifications                       |                           |  |
|---------------------------------------|---------------------------|--|
| ETIM 6                                | EC000046 - Cable tie      |  |
| ETIM 7                                | EC000046 - Cable tie      |  |
| UNSPSC                                | 39121703                  |  |
| WEEE Category                         | Product Not in WEEE Scope |  |
| IDEA Granular Category<br>Code (IGCC) | 5034 >> Cable ties        |  |

## Categories

TY232MX-RW 3

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Wire\ Management\ and\ Connectivity \rightarrow Cable\ Ties$ 

