

PRODUCT-DETAILS

TY24MX

CABLE TIE 30LB 5.5IN UV BLK NYLON



General Information

Extended Product Type	TY24MX
Product ID	7TAG009130R0009
EAN	5414363062257
Catalog Description	CABLE TIE 30LB 5.5IN UV BLK NYLON
Long Description	Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 85 Degrees Celsius (185 F) for Indoor Applications, UL/EN/CSA62275 Type 2/21 Rated for AH-2 Plenum, Length of 137mm (5.4 Inches), Width of 3.6mm (0.14 Inches), Thickness of 1mm (0.04 Inch), Tensile Strength Rating of 133 Newtons (30 Pounds), Bulk Pack

Ordering

E-Number (Finland)	1381509
EAN	5414363062257

Dimensions

Product Net Width	0.14 in 3.6 mm
Product Net Length	0, mm
Product Net Depth / Length	5.4 in 137 mm

Container Information

Package Level 1 Units	1000 piece
Package Level 1 Width	8.7 in 221 mm
Package Level 1 Height	2.7 in 69 mm
Package Level 1 Depth / Length	10.1 in 257 mm
Package Level 2 Units	10000 piece
Package Level 2 Width	10.9 in 277 mm
Package Level 2 Height	10.9 in 277 mm
Package Level 2 Depth / Length	13.2 in 335 mm

Additional Information

Bundle Diameter	0.08 to 1.38 in 2 to 35 mm
Effective Date	19680112
Lock Type	Stainless Steel Barb
Number of Batteries	0
Product Name	PLASTIC CABLE TIE
Product Type	High Performance
Special Functions	Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time.
Standards	UL E49405
Tensile Strength	30 lb 133 N
Thickness	0.04 in 1.0 mm
UPC	786210826448

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TDS000566
Declaration of Conformity - CE	9AKK107492A9841
Instructions and Manuals	TY24MX

Classifications

ETIM 6	EC000046 - Cable tie
ETIM 7	EC000046 - Cable tie
UNSPSC	39121703
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5034 >> Cable ties

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Cable Ties

