

PRODUCT-DETAILS

# **TY25MX-RW**TY25MX FOR RAILWAY

Extended Product Type	TY25MX-RW
Product ID	7TCG009210R0085
EAN	5415022180176
Catalog Description	TY25MX FOR RAILWAY
Long Description	Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 105 Degrees Celsius (22 F), Weather and Ultraviolet Resistant for Exterior Applications, Length of 185.67mm (7.31 Inches), Width of 4.67mm (0.184 Inches), Thickness of 1.09mm (0.043 Inches) Tensile Strength Rating of 220 Newtons (50 Pounds), 500 Bulk Pack

Ordering	
EAN	5415022180176

Dimensions	
Product Net Width	0.184 in 4.67 mm
Product Net Depth / Length	7.3 in 185.67 mm
Product Net Weight	.003 lb 1.361 g

#### **Container Information**

Package Level 1 Units	1000 piece
Package Level 1 Width	10.21 in
	259 mm
Package Level 1 Height	1.96 in
	50 mm
Package Level 1 Depth /	14.14 in
Length	359 mm
Package Level 2 Units	10000 piece
Package Level 2 Width	14.7 in
	373 mm
Package Level 2 Height	9.5 in
	241 mm
Package Level 2 Depth /	21.2 in
Length	538 mm

### **Additional Information**

Brand / Label	Ty-Rap
Bundle Diameter	0.12 to 1.89 in
	3 to 48 mm
Color	Black
Material	Nylon/Polyamide 6.6
Number of Batteries	0
Product Name	OTHER ARTICLES OF PLASTIC
Product Type	Railway
Special Functions	Low profile head is designed to prevent snags on uneven surfaces and
	easier to pull through bulkheads. Non-magnetic stainless steel locking
	device insures both maximum strength and the right tightness every time.
Standards	UL E49405
Tensile Strength	50 lb
	220 N
Thickness	0.043 in
	1.09 mm
UPC	786209716705

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TY25MX-RW
Instructions and Manuals	TY25MX-RW

## Classifications

ETIM 6	EC000046 - Cable tie
ETIM 7	EC000046 - Cable tie
UNSPSC	39121703
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5034 >> Cable ties

## Categories

TY25MX-RW 3

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Wire\ Management\ and\ Connectivity \rightarrow Cable\ Ties$ 

