



PRODUCT-DETAILS

TY524MXR-RW

TY24MX FOR RAILWAY SP



General Information

Extended Product Type	TY524MXR-RW
Product ID	7TCG009130R0013
EAN	5415022243529
Catalog Description	TY24MX FOR RAILWAY SP
Long Description	Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 105 Degrees Celsius (221 F), Weather and Ultraviolet Resistant for Exterior Applications, Length of 139.7mm (5.5 Inches), Width of 3.56mm (0.14 Inch), Thickness of 1.31mm (0.052 Inch), Tensile Strength Rating of 180 Newtons (40 Pounds)

Ordering

EAN	5415022243529
-----	---------------

Dimensions

Product Net Width	0.14 in 3.56 mm
Product Net Length	0, mm
Product Net Depth / Length	5.5 in 139.7 mm

Container Information

Package Level 1 Units	100 piece
-----------------------	-----------

Package Level 1 Width	5.5 in 140 mm
Package Level 1 Height	0.39 in 10 mm
Package Level 1 Depth / Length	9.82 in 249 mm
Package Level 2 Units	10000 piece
Package Level 2 Width	10.21 in 259 mm
Package Level 2 Height	14.14 in 359 mm
Package Level 2 Depth / Length	19.65 in 499 mm

Additional Information

Brand / Label	Ty-Rap
Color	Black
Effective Date	20140611
Lock Type	Stainless Steel Barb
Material	Nylon/Polyamide 6.6
Number of Batteries	0
Product Name	OTHER ARTICLES OF PLASTIC
Product Type	Railway
Special Functions	Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time.
Tensile Strength	40 lb 180 N
Thickness	0.052 in 1.32 mm
UPC	786209884107

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TDS000566
Instructions and Manuals	TY524MXR-RW

Classifications

ETIM 6	EC000046 - Cable tie
ETIM 7	EC000046 - Cable tie
UNSPSC	39121703
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5034 >> Cable ties

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Cable Ties

