



PRODUCT-DETAILS

TY525MXR-RW

TY25MX FOR RAILWAY SP



General Information

Extended Product Type	TY525MXR-RW
Product ID	7TCG009210R0088
EAN	5415022243581
Catalog Description	TY25MX FOR RAILWAY SP
Long Description	Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 105 Degrees Celsius (221 F), Weather and Ultraviolet Resistant for Exterior Applications, Length of 185.67mm (7.31 Inches), Width of 4.67mm (0.184 Inches), Thickness of 1.09mm (0.043 Inches), Tensile Strength Rating of 220 Newtons (50 Pounds)

Ordering

EAN	5415022243581
-----	---------------

Dimensions

Product Net Width	0.184 in 4.67 mm
Product Net Depth / Length	7.31 in 185.67 mm
Product Net Weight	.003 lb 1.361 g

Container Information

Package Level 1 Units	100 piece
Package Level 1 Width	5.1 in 130 mm
Package Level 1 Height	0.78 in 20 mm
Package Level 1 Depth / Length	11 in 279 mm
Package Level 2 Units	10000 piece
Package Level 2 Width	14 in 356 mm
Package Level 2 Height	10.5 in 267 mm
Package Level 2 Depth / Length	20.9 in 531 mm

Additional Information

Brand / Label	Ty-Rap
Color	Black
Lock Type	Stainless Steel Barb
Material	Nylon/Polyamide 6.6
Number of Batteries	0
Product Name	OTHER ARTICLES OF PLASTIC
Product Type	Railway
Special Functions	Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time.
Tensile Strength	50 lb 220 N
Thickness	0.043 in 1.09 mm
UPC	786209884183

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TY525MXR-RW
Instructions and Manuals	TY525MXR-RW

Classifications

ETIM 6	EC000046 - Cable tie
ETIM 7	EC000046 - Cable tie
UNSPSC	39121703
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5034 >> Cable ties

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Cable Ties

