

770.61 mm

PRODUCT-DETAILS

TY529M

Length

CBL TIE 120LB 30IN NATURAL NYLON

| General Information | |
|------------------------------------|--|
| Extended Product Type | TY529M |
| Product ID | 7TAG009280R0003 |
| EAN | 5414363065944 |
| Catalog Description | CBL TIE 120LB 30IN NATURAL NYLON |
| Long Description | Cable Tie, Natural Polyamide (Nylon 6.6) for Temperatures up to 85 Degrees Celsius (185 F) for Indoor Applications, UL/EN/CSA62275 Type 2/21S Rated for AH-2 Plenum and as a Flexible Cable and Conduit Support, Length of 770.61mm (30.34 Inches), Width of 6.93mm (0.273 Inches), Thickness of 1.52mm (0.06 Inches), Tensile Strength Rating of 534 Newtons (120 pounds) |
| | |
| | |
| Ordering | |
| Ordering E-Number (Finland) | 1381534 |
| | 1381534 5414363065944 |
| E-Number (Finland) | |
| E-Number (Finland) EAN | 5414363065944 0.273 in |
| E-Number (Finland) EAN Dimensions | |

| Container Information | |
|-----------------------------------|--------------------|
| Package Level 1 Units | 50 piece |
| Package Level 1 Width | 6 in 152 mm |
| Package Level 1 Depth / Length | 36 in 914 mm |
| Package Level 2 Units | 500 piece |
| Package Level 2 Width | 6.25 in 159 mm |
| Package Level 2 Height | 4.75 in 121 mm |
| Package Level 2 Depth / Length | 34.25 in 870 mm |

| Additional Information | |
|------------------------|--|
| Brand / Label | Ty-Rap |
| Bundle Diameter | 0.236 to 9.01 in 6 to 229 mm |
| Color | Natural |
| Effective Date | 19680502 |
| Lock Type | Stainless Steel Barb |
| Material | Nylon/Polyamide 6.6 |
| Number of Batteries | 0 |
| Product Name | NYLON CABLE TIES AND ACCESSORIES |
| Product Type | High Performance |
| Special Functions | Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time. |
| Standards | UL E49405 |
| Tensile Strength | 120 lb 530 N |
| Thickness | 0.06 in 1.52 mm |
| UPC | 786210830735 |

| Certificates and Declarations (Document Number) | | | |
|---|-----------------|--|--|
| Data Sheet, Technical Information | TY529M | | |
| Declaration of Conformity - CE | 9AKK107492A9841 | | |
| Instructions and Manuals | ТҮ529М | | |

| Classifications | | | | |
|---------------------------------------|---------------------------|--|--|--|
| ETIM 6 | EC000046 - Cable tie | | | |
| ETIM 7 | EC000046 - Cable tie | | | |
| UNSPSC | 39121703 | | | |
| WEEE Category | Product Not in WEEE Scope | | | |
| IDEA Granular Category Code (IGCC) | 5034 >> Cable ties | | | |

TY529M 3

| _ | | | | | | | | |
|----|---|---|---|---|---|----|---|---|
| C. | a | t | ρ | a | റ | ri | e | S |
| | | | | | | | | |

 $Low\ Voltage\ Products\ and\ Systems\ \rightarrow Installation\ Products\ \rightarrow\ Wire\ Management\ and\ Connectivity\ \rightarrow\ Cable\ Ties$