


UGT521

Ultrasonic sensor

UGB00300FOKG/US



1 LEDs



Electrical data

Operating voltage	[V]	10...30 DC; ("supply class 2" to cULus)
Current consumption	[mA]	< 35
Protection class		III
Reverse polarity protection		yes
Power-on delay time	[s]	0.1
Converter frequency	[kHz]	300

Inputs

Synchronisation input	no
Multiplex input	no

Outputs

Electrical design	NPN
Output function	normally open / normally closed; (parameterisable)
Max. voltage drop switching output DC	[V] 2.2
Permanent current rating of switching output DC	[mA] 100
Switching frequency DC	[Hz] 8
Short-circuit protection	yes
Overload protection	yes

Detection zone

Sensing range	[mm] 40...300
Blind zone	[mm] 40
Angle of aperture cylindrical	[°] 7; (±2)
Detection range hysteresis	[mm] < 1
Max. deviation from the 90° angle sensor/object	[°] ± 4

UGT521



Ultrasonic sensor


UGB00300FOKG/US

Accuracy / deviations		
Notes on the accuracy / deviation	The indicated values are reached after a warm-up time of 20 minutes.	
Temperature compensation	yes	
Hysteresis [%]	< 1	
Switch point drift [%]	-2.5...2.5	
Linearity error of analogue output [%]	< 1	
Operating conditions		
Ambient temperature [°C]	-20...70	
Protection	IP 67	
Tests / approvals		
EMC	EN 61000-4-2 ESD	4 kV CD / plastics
		8 kV AD / metal
	EN 61000-4-3 HF radiated	3 V/m
	EN 61000-4-4 Burst	2 kV
	EN 61000-4-6 HF conducted	3 V
	EN 55011	Class A
Vibration resistance	EN 60068-2-6 Fc	(10-55) Hz 1 mm amplitude, oscillation period 5 min., 30 min. per axis at resonance or 55 Hz
Shock resistance	EN 60068-2-27 Ea	yes
MTTF [years]	215	
Mechanical data		
Weight [g]	79	
Housing	threaded type	
Dimensions [mm]	M18 x 1 / L = 60.5	
Thread designation	M18 x 1	
Materials	stainless steel (1.4404 / 316L); PA; epoxy glass ceramics	
Displays / operating elements		
Display	switching status	1 LED, yellow
	echo	1 LED, green
Accessories		
Accessories (supplied)	lock nuts: 2, stainless steel	
Remarks		
Remarks	operating voltage "supply class 2" according to cULus	
Pack quantity	1 pcs.	
Electrical connection		
Connector: 1 x M12		
		

Ultrasonic sensor

UGB00300FOKG/US



Connection



2: Teach



Diagrams and graphs



- 1: distance
- 2: Detection zone
- 3: switch-on/switch-off graph
- 4: Target 100 x 100 mm
- 5: 50 % of the target in the detection zone
- 6: switch point