## Product data sheet Characteristics

## VW3A3320

## EtherNet/IP communication card - 2 RJ 45 connectors



Main	
Product or component type	Communication card
Range compatibility	Altivar 61 Altivar 71
Communication port protocol	Ethernet/IP
Connector type	2 RJ45 connectors
Transmission rate	10/100 Mbps
Physical interface	IEEE 802.3 for Ethernet IP/Modbus TCP
Web services	Altivar chart Altivar viewer Data editor Drive monitor Drive parameters Drive recorder E-mail Ethernet/IP scanner setup Ethernet statistics FDR Agent Message statistics Security Modbus TCP scanner setup

## Complementary

Complementary		
Exchange mode	Half duplex and full duplex	
Communication data link	LLC : IEEE 802.2	
	MAC : IEEE 802.3	
Communication network type	ICMP	
	IP conforming to RFC791	
Communication transport type	TCP conforming to RFC793	
	UDP	
Web server	Embedded	
Communication service	Read device identification (43/14)	
	Ethernet/IP adapter	
	Write single register (06)	
	Write multiple registers (16)	
	TFTP	
	SNMP	
	Read/Write multiple registers (23)	
	Read input registers (04)	
	Read holding registers (03)	
	FTP	
	Diagnostics (08)	
	CIP AC Drive (02) profile	
	I/O profile	
	CiA 402 profile	
Display type	Graphic display terminal for reference received	
	Graphic display terminal for number of frames received	
	Graphic display terminal for control word received	
	1 LED for TX/RX (Transmit/Receive port 2)	
	1 LED for TX/RX (Transmit/Receive port 1)	
	1 LED for NS (Network Status)	
	1 LED for MS (Module Status)	
	1 LED for Link (Link Status)	
Product weight	0.3 kg	