



### Main

|                           |                      |
|---------------------------|----------------------|
| Range of product          | Altivar              |
| Product or component type | Communication module |

### Complementary

|                             |                                                                                                                                                         |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range compatibility         | Altivar 32<br>Altivar Process ATV600<br>Altivar Process ATV900<br>Altivar Machine ATV320                                                                |
| Communication port protocol | Profinet<br>Link Layer Discovery Protocol                                                                                                               |
| Electrical connection       | 2 connectors RJ45 Ethernet                                                                                                                              |
| Transmission rate           | 100 Mbits                                                                                                                                               |
| Web server                  | Embedded HTTP server                                                                                                                                    |
| Web services                | Data editor<br>Drive monitor<br>Drive parameters<br>Drive recorder<br>Ethernet statistics<br>IPar client settings<br>Save/Restore drive configuration   |
| Display type                | 1 LED for MS (Module Status)<br>1 LED for NS (Network Status)<br>1 LED for TX/RX (Transmit/Receive port 1)<br>1 LED for TX/RX (Transmit/Receive port 2) |
| Bus profile                 | PROFIdrive                                                                                                                                              |
| Standards                   | IEC 61800-7-201 (CiA 402)                                                                                                                               |
| Product weight              | 0.3 kg                                                                                                                                                  |