


ATV cabinets



Main

Product or component type	Communication card
Range compatibility	Altivar 61 Plus Altivar 71 Plus
Communication port protocol	Ethernet/IP
Connector type	2 RJ45 connectors
Transmission rate	10 Mbps 100 Mbps
Physical interface	IEEE 802.3
Web services	Drive monitor Drive parameters Drive recorder E-mail Ethernet/IP scanner setup Ethernet/IP setup Ethernet statistics Message statistics Security

Complementary

Exchange mode	Half duplex and full duplex
Communication data link	LLC : IEEE 802.2 MAC : IEEE 802.3
Communication network type	ICMP IP conforming to RFC791
Communication transport type	TCP conforming to RFC793 UDP
Web server	Embedded
Communication service	DHCP CIP I/O data BOOTP CIP AC Drive (02) profile Allen-Bradley drive profile I/O profile CiA 402 profile
Display type	Graphic display terminal for reference received Graphic display terminal for number of frames received Graphic display terminal for control word received 1 LED for TX/RX (Transmit/Receive port 2) 1 LED for TX/RX (Transmit/Receive port 1) 1 LED for NS (Network Status) 1 LED for MS (Module Status) 1 LED for Link (Link Status)
Product weight	0.3 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.