


ATV cabinets



Main

Product or component type	Encoder interface cards with RS422 compatible differential outputs
Range compatibility	Altivar 71 Plus
[Us] rated supply voltage	15 V DC (voltage limits: 15...16 V)
Number of pulses per revolution	<= 5000 <= 10000

Complementary

Supply current	<= 0.175 A
Protection type	Overload protection Short-circuit protection
Cable length	<= 100 m
Maximum operating frequency	300 kHz
Input signal	A B Compliment of A Compliment of B
Input impedance	1000 Ohm
Electrical connection	Terminal, connection capacity: 0.2 mm ² (AWG 24) (encoder consumption of 175 mA) at 8 V Terminal, connection capacity: 0.2 mm ² (AWG 24) (encoder consumption of 100 mA) at 8 V Terminal, connection capacity: 0.2 mm ² (AWG 24) (encoder consumption of 175 mA) at 8 V Terminal, connection capacity: 0.2 mm ² (AWG 24) (encoder consumption of 100 mA) at 8 V Terminal, connection capacity: 0.2 mm ² (AWG 24) (encoder consumption of 175 mA) at 8 V Terminal, connection capacity: 0.2 mm ² (AWG 24) (encoder consumption of 100 mA) at 8 V
Product weight	0.2 kg