



Main

Range of product	Altivar
Product or component type	Line choke
Product compatibility	ATV71HD45M3X - line choke - 1 per drive ATV71HD37M3X - line choke - 1 per drive ATV71HD30M3X - line choke - 1 per drive ATV71HD22M3X - line choke - 1 per drive ATV71HD18M3X - line choke - 1 per drive ATV61WD75N4C - line choke - 1 per drive ATV61WD75N4 - line choke - 1 per drive ATV61HD75N4 - line choke - 1 per drive ATV61HD45M3X - line choke - 1 per drive ATV61HD37M3X - line choke - 1 per drive ATV61HD30M3X - line choke - 1 per drive ATV61HD22M3X - line choke - 1 per drive ATV61HD18M3X - line choke - 1 per drive
Number of phases	Three phase
Range compatibility	Altivar 61 Altivar 71
Product specific application	Reduction of current harmonics
Value of inductance	0.15 mH
[In] rated current	230 A
Thermal losses	400 W
Electrical connection	Bare wires, Ø = 9 mm

Complementary

Power supply frequency	50...60 Hz
Max current	1.65 x nominal current for 60 s
Voltage drop at rated load	3...5 %
Electrical insulation class	Class F
Clearance distance	5.5 mm conforming to IEC 60664
Leakage distance	11.5 mm conforming to IEC 60664
Product weight	45 kg
Width	320 mm
Height	340 mm
Depth	240 mm

Environment

Standards	EN 50178 IEC 60076 (with HD398) VDE 0160 level 1
IP degree of protection	IP00 (terminals) IP00 (choke)
Environmental characteristic	3S1 conforming to IEC 721-3-3 3C2 conforming to IEC 721-3-3 3B1 conforming to IEC 721-3-3
Pollution degree	2 conforming to EN 50178
Vibration resistance	1.5 mm peak to peak (f = 3...13 Hz) conforming to IEC 60068-2-6 1 gn (f = 13...200 Hz) conforming to IEC 60068-2-6
Shock resistance	15 gn for 11 ms conforming to IEC 60068-2-27
Relative humidity	<= 95 %
Ambient air temperature for operation	0...45 °C without current derating > 45...< 55 °C with current derating of 2 % per °C

Ambient air temperature for storage	-25...70 °C
Operating altitude	1000...3000 m with current derating 1 % per 100 m <= 1000 m without current derating

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 0801 - Schneider Electric declaration of conformity