


Product data sheet

Characteristics

VW3A4671

passive filter - 370 A - 460 V - for variable speed drive



Main

Product or component type	Passive filter
Product specific application	Reduction of current harmonics

Complementary

Range compatibility	Altivar 61 Altivar 71
[Us] rated supply voltage	480 V (+/- 10 %)
Power supply frequency	60 Hz (tolerance: +/- 5 %)
Quantity per drive	2 filters per drive for ATV71HC50N4 2 filters per drive for ATV61HC50N4 1 filter per drive for ATV71HC25N4 1 filter per drive for ATV71HC20N4 1 filter per drive for ATV61HC22N4
[In] rated current	370 A
Network number of phases	3 phases
THDI	5 % for ATV71HC20N4 ATV71H motor: 200 kW / 300 hp 5 % for ATV61HC22N4 ATV61H motor: 220 kW / 350 hp 5 % for ATV71HC50N4 ATV71H motor: 500 kW / 700 hp 5 % for ATV61HC50N4 ATV61H motor: 500 kW / 700 hp 5 % for ATV71HC25N4 ATV71H motor: 250 kW / 400 hp
Max current	1.5 x nominal current
Efficiency	98 %
Cos phi	0.99 at 100 % of line current 0.85 at 75 % of line current 1 at 150 % of line current
Electrical connection	Bare wires, Ø = 16.5 mm
Electrical insulation class	Class F
Product weight	250 kg

Environment

IP degree of protection	IP20
Relative humidity	5...85 % without condensation
Ambient air temperature for operation	5...40 °C without current derating > 40...55 °C with current derating 3 % per °C
Ambient air temperature for storage	> -25...55 °C
Operating altitude	> 1000...4000 m with current derating 5 % per 1000 m <= 1000 m without current derating