



### Main

|                           |                                                                                                                                                                                                    |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range of product          | Altivar                                                                                                                                                                                            |
| Product or component type | ATV71 hoist resistor                                                                                                                                                                               |
| Range compatibility       | Altivar 71                                                                                                                                                                                         |
| Product compatibility     | ATV71WU22N4<br>ATV71WU15N4<br>ATV71PU22N4Z<br>ATV71PU15N4Z<br>ATV71HU15S6X<br>ATV71W075N4<br>ATV71P075N4Z<br>ATV71HU22Y<br>ATV71HU22N4<br>ATV71HU15N4<br>ATV71H075N4<br>ATV71H075M3<br>ATV71H037M3 |
| Average power available   | 1.6 kW at 50 °C                                                                                                                                                                                    |
| Ohmic value               | 100 Ohm                                                                                                                                                                                            |

### Complementary

|                       |                                               |
|-----------------------|-----------------------------------------------|
| Electrical connection | Bar wire with M6 screw                        |
| Protection type       | Thermal protection via thermal overload relay |
| Product weight        | 6 kg                                          |

### Environment

|                                       |                                                            |
|---------------------------------------|------------------------------------------------------------|
| Ambient air temperature for operation | 0...50 °C                                                  |
| Ambient air temperature for storage   | -25...75 °C                                                |
| IP degree of protection               | IP23 (horizontal)<br>IP20 (any position except horizontal) |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.