



Main

Product or component type	Pre-assembled cable kits for motion sequence with 2 I/O, 1 STO insert
Accessory / separate part type	Cable
Accessory / separate part category	Connection accessories
Accessory / separate part destination	For drives with printed circuit board connectors
Cable length	5 m
Additional information	With integrated cable entry with strain relief With insert equipped with 2 I/O and 1 safe torque off via M8 connector

Complementary

Range compatibility	Lexium ILA Lexium ILE Lexium ILS
Communication interface	I/O for motion sequence
Electrical connection	Cable end open Printed circuit board connector for drive

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0932 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available Download Product Environmental
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.