# Product datasheet Characteristics

## VW3M5D1FR30

power cable 3m shielded 4x 0,82mm<sup>2</sup>, BCH2 brake leads connection



Main	
Range of product	Lexium 28
Product or component type	Power cable
Accessory / separate part type	Preassembled power cordset
Accessory / separate part category	Connection accessory
Product compatibility	Servo motor BCH2 at 50 W (40 mm) (with brake) Servo motor BCH2 at 100 W (40 mm) (with brake) Servo motor BCH2 at 200 W (60 mm) (with brake) Servo motor BCH2 at 400 W (60 mm) (with brake) Servo motor BCH2 at 400 W (80 mm) (with brake) Servo motor BCH2 at 400 W (80 mm) (with brake) Servo motor BCH2 at 750 W (80 mm) (with brake)
Accessory / separate part destination	Between servo motor and servo drive
Range compatibility	Lexium 28
Cable length	3 m

#### Complementary

Complementary		{
Electrical connection	Free end for servo drive side Connector - Molex 6-pin for servo motor side	
AWG gauge	6 x AWG 18	
Product weight	0.3 kg	<u> </u>

### Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	

#### Contractual warranty

Contractad Warranty		
Warranty	18 months	