Product datasheet Characteristics

VW3M5D2FR50

power cable 5m shielded 4x 1,3mm², BCH2 brake MIL connector



П	٧	1	a	u	ı

Range of product	Lexium 28	
Product or component type	Power cable	
Accessory / separate part type	Preassembled power cordset	
Accessory / separate part category	Connection accessory	
Product compatibility	Servo motor BCH2 at 1000 W (100 mm) (with brake) Servo motor BCH2 at 2000 W (100 mm) (with brake) Servo motor BCH2 at 300 W (130 mm) (with brake) Servo motor BCH2 at 500 W (130 mm) (with brake) Servo motor BCH2 at 600 W (130 mm) (with brake) Servo motor BCH2 at 850 W (130 mm) (with brake) Servo motor BCH2 at 850 W (130 mm) (with brake) Servo motor BCH2 at 900 W (130 mm) (with brake) Servo motor BCH2 at 1000 W (130 mm) (with brake) Servo motor BCH2 at 1500 W (130 mm) (with brake) Servo motor BCH2 at 2000 W (130 mm) (with brake)	
Accessory / separate part destination	Between servo motor and servo drive	
Range compatibility	Lexium 28	
Cable length	5 m	

Complementary

Electrical connection	Free end for servo drive side Connector - MIL small for servo motor side	
AWG gauge	6 x AWG 16	
Product weight	0.9 kg	

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	Yes	:
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	

Warranty 18 months