



Main

Range of product	Lexium 32i
Product or component type	Connector module
Accessory / separate part category	Connection accessories
Electrical connection	Industrial connector


Complementary

Product compatibility	Drive control unit LXM32i EtherCAT
Accessory / separate part destination	Motor BMI with drive control unit Lexium 32i
Range compatibility	Lexium 32i
Communication interface	EtherCAT
Input/Output type	4 discrete inputs
Discrete input logic	Source
Safety function	STO (safe torque off)

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1301 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available Download Product Environmental
Product end of life instructions	Available Download End Of Life Manual

Connection of I/O Module for EtherCAT with Industrial Connectors



(1)	IN
(2)	OUT
+24VDC	24 V signal power supply
0VDC	Reference potential to +24VDC
DI0	Digital input 0
DI1	Digital input 1
DI2	Digital input 2
DI3	Digital input 3
STO_A	Safety function STO
STO_COM	Reference potential for safety function STO
STO_B	Safety function STO
SHLD	Shield (grounded internally)
Tx+	Ethernet transmit signal +
Tx-	Ethernet transmit signal -
Rx+	Ethernet receive signal +
Rx-	Ethernet receive signal -
NC	Not connected