## Product data sheet Characteristics

# VZ1L004M010

line choke - 10 mH - 4 A - 1 phase - 17 W - for variable speed drive



### Main

Product or component type	Line choke
Product compatibility	ATV32H037M2 - line choke - 1 per drive ATV32H018M2 - line choke - 1 per drive ATV31C037M2 - line choke - 1 per drive ATV31C018M2 - line choke - 1 per drive ATV312H037M2 - line choke - 1 per drive ATV312H018M2 - line choke - 1 per drive
Number of phases	Single phase
Range compatibility	Altivar 312 Altivar 32 Altivar 31C Altivar 312 Solar
Product specific application	Reduction of current harmonics
Value of inductance	10 mH
[In] rated current	4 A
Thermal losses	17 W

### Complementary

Power supply frequency	5060 Hz	4
Voltage drop at rated load	35 %	
Product weight	0.63 kg	
Width	60 mm	
Height	100 mm	
Depth	80 mm	

### Environment

Standards	EN 50178 IEC 60076 (with HD398) VDE 0160 level 1	
IP degree of protection	IP20 (terminals) IP00 (choke)	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or intendity or the see applications. This documentation is not integrated to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.