Product data sheet Characteristics

WB1KB134

coil WB1 - 220...230 V 50...400 Hz, 110...125 V



Main

Range of product	TeSys B
Product or component type	Contactor coil
Product compatibility	CR1B
Control circuit type	AC
Coil type	Low consumption
[Uc] control circuit voltage	110125 V DC

Complementary

Control circuit voltage limits	95108 V
Average resistance	25.2 Ohm at 20 °C
Inrush power in VA	450620 VA 1P
Inrush power in W	380520 W for 1P
Hold-in power consumption in VA	0.150.2 VA 50400 Hz 1P
Hold-in power consumption in W	0.150.2 W for 1P
Operating time	25 ms sealed
Mechanical durability	1200000 cycles
Operating rate	<= 120 cyc/mn at <= 55 °C
Product weight	1.12 kg

Offer Sustainability

Sustainable offer status	Not Green Premium product	
RoHS	Will not be Compliant	

Contractual warranty

Contractidal warranty		
Period	18 months	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherenced as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the documentation is not be used to perform the appropriate and complete risk analysis, evaluation of the products with respect to the relevant specific application or use thereof. Neither Schmeider Electric Industries SAS nor any of its affiliates or substitatives shall be responsible or liable for misuse of the information contained herein.