

### Main

|                              |                 |
|------------------------------|-----------------|
| Range of product             | TeSys B         |
| Product or component type    | Contacteur coil |
| Product compatibility        | CR1B            |
| Control circuit type         | AC              |
| Coil type                    | Low consumption |
| [Uc] control circuit voltage | 47...50 V DC    |

### Complementary

|                                 |                           |
|---------------------------------|---------------------------|
| Average resistance              | 1.85 Ohm at 20 °C         |
| Inrush power in VA              | 1100...1300 VA 3P         |
| Inrush power in W               | 900...1100 W for 3P       |
| Hold-in power consumption in VA | 0.7...1 VA 50...400 Hz 3P |
| Hold-in power consumption in W  | 0.7...1 W for 3P          |
| Operating time                  | 25 ms sealed              |
| Mechanical durability           | 1200000 cycles            |
| Operating rate                  | <= 120 cyc/mn at <= 55 °C |
| Product weight                  | 1.12 kg                   |

### Environment

|                  |              |
|------------------|--------------|
| Heat dissipation | 24...30 W 3P |
|------------------|--------------|

### Offer Sustainability

|                          |                           |
|--------------------------|---------------------------|
| Sustainable offer status | Not Green Premium product |
| RoHS                     | Will not be Compliant     |

### Contractual warranty

|        |           |
|--------|-----------|
| Period | 18 months |
|--------|-----------|