

XALFK3011E

pit switch box XAL-F - for lift inspection - 1 flush pushbutton - spring return



Main

Range of product	Harmony XALF
Product or component type	Pit switch box
Device short name	XALF
Product specific application	Lift inspection
Operator profile	1 illuminated mushroom head - 2 flush pushbuttons - 1 power socket
Contacts operation	Slow-break

Complementary

Material	Polycarbonate
Product weight	0.55 kg
Marking	CE
Contacts material	Silver alloy (Ag/Ni)
Light source colour	White

Environment

Protective treatment	TH
Ambient air temperature for storage	-40...70 °C
Ambient air temperature for operation	0...50 °C
Standards	EN 81-1 EN/IEC 60947-1 EN/IEC 60947-5-1 EN/IEC 60947-5-4 EN/IEC 60947-5-5

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Dimensions

