Product data sheet Characteristics

XALFKT6442

hoistway box XAL-F for lift inspection - 1 mushroom head emergency stop pb- 1 NC



| Main | |
|------------------------------|----------------------------|
| Range of product | Harmony XALF |
| Product or component type | Hoistway box |
| Device short name | XALF |
| Product specific application | Lift inspection |
| Operator profile | 1 mushroom head pushbutton |
| Operator description | Red unmarked 1 NC |
| Contacts operation | Slow-break |

Complementary

| Material | Polycarbonate |
|-------------------|----------------------|
| Product weight | 0.155 kg |
| Marking | CE |
| Contacts material | Silver alloy (Ag/Ni) |

Environment

| Protective treatment | TH |
|---------------------------------------|---------------------------|
| Ambient air temperature for storage | -4070 °C |
| Ambient air temperature for operation | 050 °C |
| Standards | EN 81-1 EN/IEC 60947-1 |
| | EN/IEC 60947-5-1 |
| | EN/IEC 60947-5-4 |
| | EN/IEC 60947-5-5 |

Product data sheet **Dimensions Drawings**


XALFKT6442

Dimensions









- 2 knock-outs for Pg 13.5 cable gland, maximum capacity 12 mm / 0.47 in. Knock-out for cable entry, maximum capacity 14 mm / 0.55 in.