



## Main

|                             |                                                                 |
|-----------------------------|-----------------------------------------------------------------|
| Range of product            | Harmony XALK                                                    |
| Product or component type   | Complete control station                                        |
| Device short name           | XALK                                                            |
| Product destination         | For XB5 Ø 22 mm control and signalling units                    |
| Control station application | Emergency stop function<br>Emergency switching off function     |
| Colour of base of enclosure | Light grey RAL 7035                                             |
| Colour of cover             | Yellow RAL 1021                                                 |
| Material                    | Polycarbonate                                                   |
| Operator profile            | 1 mushroom head pushbutton                                      |
| Operators description       | Red unmarked 1 NO + 2 NC                                        |
| Reset                       | Turn to release                                                 |
| Control station composition | 1 mushroom head Ø 40 mm push-button, red - 1 NO + 2 NC unmarked |
| Contacts operation          | Slow-break                                                      |

## Complementary

|                                                          |                                                                                                                                                                                                                                                                                                                                                                          |
|----------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Cable entry                                              | 2 knock-outs for Pg 13 cable gland and ISO M20 <= 12 mm<br>1 knock-out for cable entry <= 14 mm                                                                                                                                                                                                                                                                          |
| Product weight                                           | 0.194 kg                                                                                                                                                                                                                                                                                                                                                                 |
| Resistance to high pressure washer                       | 7000000 Pa at 55 °C, 0.1 m                                                                                                                                                                                                                                                                                                                                               |
| Positive opening                                         | With conforming to EN/IEC 60947-5-1 appendix K                                                                                                                                                                                                                                                                                                                           |
| Operating travel                                         | 4.3 mm total travel<br>2.6 mm NO changing electrical state<br>1.5 mm NC changing electrical state                                                                                                                                                                                                                                                                        |
| Operating force                                          | 44 N NC + NO changing electrical state                                                                                                                                                                                                                                                                                                                                   |
| Mechanical durability                                    | 300000 cycles                                                                                                                                                                                                                                                                                                                                                            |
| Connections - terminals                                  | Screw clamp terminals >= 1 x 0.22 mm <sup>2</sup> without cable end conforming to EN/IEC 60947-1<br>Screw clamp terminals <= 2 x 1.5 mm <sup>2</sup> with cable end conforming to EN/IEC 60947-1                                                                                                                                                                         |
| Tightening torque                                        | 0.8...1.2 N.m conforming to EN/IEC 60947-1                                                                                                                                                                                                                                                                                                                               |
| Shape of screw head                                      | Slotted flat Ø 5.5 mm<br>Slotted flat Ø 4 mm<br>Cross pozidriv No 1<br>Cross Philips no 1                                                                                                                                                                                                                                                                                |
| Contacts material                                        | Silver alloy (Ag/Ni)                                                                                                                                                                                                                                                                                                                                                     |
| Short circuit protection                                 | 10 A cartridge fuse, gG conforming to EN/IEC 60947-5-1                                                                                                                                                                                                                                                                                                                   |
| [I <sub>th</sub> ] conventional free air thermal current | 10 A conforming to EN/IEC 60947-5-1                                                                                                                                                                                                                                                                                                                                      |
| [U <sub>i</sub> ] rated insulation voltage               | 600 V, degree of pollution: 3 conforming to EN/IEC 60947-1                                                                                                                                                                                                                                                                                                               |
| [U <sub>imp</sub> ] rated impulse withstand voltage      | 6 kV conforming to EN/IEC 60947-1                                                                                                                                                                                                                                                                                                                                        |
| [I <sub>e</sub> ] rated operational current              | 1.2 A at 600 V AC-15, A600 conforming to EN/IEC 60947-5-1<br>0.55 A at 125 V DC-13, Q600 conforming to EN/IEC 60947-5-1<br>0.27 A at 250 V DC-13, Q600 conforming to EN/IEC 60947-5-1<br>0.1 A at 600 V DC-13, Q600 conforming to EN/IEC 60947-5-1<br>6 A at 120 V AC-15, A600 conforming to EN/IEC 60947-5-1<br>3 A at 240 V AC-15, A600 conforming to EN/IEC 60947-5-1 |

|                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|--------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Electrical durability                | 1000000 cycles DC-13 at 0.5 A 24 V at 3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C<br>1000000 cycles DC-13 at 0.2 A 110 V at 3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C<br>1000000 cycles AC-15 at 4 A 24 V at 3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C<br>1000000 cycles AC-15 at 3 A 120 V at 3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C<br>1000000 cycles AC-15 at 2 A 230 V at 3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C |
| Electrical reliability IEC 60947-5-4 | $\Lambda < 10\exp(-8)$ at 17 V and 5 mA conforming to EN/IEC 60947-5-4<br>$\Lambda < 10\exp(-6)$ at 5 V and 1 mA conforming to EN/IEC 60947-5-4                                                                                                                                                                                                                                                                                                                                                                                                                           |

## Environment

|                                            |                                                                                                                                                                                |
|--------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Protective treatment                       | TH                                                                                                                                                                             |
| Ambient air temperature for storage        | -40...70 °C                                                                                                                                                                    |
| Ambient air temperature for operation      | -25...70 °C                                                                                                                                                                    |
| Class of protection against electric shock | Class II conforming to IEC 60536                                                                                                                                               |
| IP degree of protection                    | IP66 conforming to IEC 60529                                                                                                                                                   |
| NEMA degree of protection                  | NEMA 4X<br>NEMA 13                                                                                                                                                             |
| IK degree of protection                    | IK03 conforming to EN 50102                                                                                                                                                    |
| Standards                                  | EN/IEC 60204-1<br>EN/IEC 60947-1<br>EN/IEC 60947-5-1<br>EN/IEC 60947-5-4<br>EN/IEC 60947-5-5<br>EN/ISO 13850<br>IEC 60364-5-53<br>JIS C 4520<br>UL 508<br>CSA C22.2 No 14      |
| Product certifications                     | CSA<br>UL listed                                                                                                                                                               |
| Vibration resistance                       | 5 gn (f = 12...500 Hz) conforming to IEC 60068-2-6                                                                                                                             |
| Shock resistance                           | 50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC 60068-2-27<br>30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC 60068-2-27 |

## Offer Sustainability

|                                  |                                                                                       |
|----------------------------------|---------------------------------------------------------------------------------------|
| Sustainable offer status         | Green Premium product                                                                 |
| RoHS (date code: YYWW)           | Compliant - since 0807 - <a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold                                     |
| Product environmental profile    | Available <a href="#">Download Product Environmental</a>                              |
| Product end of life instructions | Need no specific recycling operations                                                 |

## Dimensions



- (1) 2 knock-outs for Pg 13.5 cable gland, maximum capacity 12 mm/0.47 in.  
(2) Knock-out for cable entry, maximum capacity 14 mm/0.55 in.

| Control station fitted with:                              | c in mm | c in in. |
|-----------------------------------------------------------|---------|----------|
| Flush pushbutton                                          | 62      | 2.44     |
| Pilot light                                               | 64      | 2.52     |
| Illuminated pushbutton                                    | 65.5    | 2.58     |
| Projecting pushbutton                                     | 66      | 2.60     |
| Selector switch                                           | 80      | 3.15     |
| Mushroom head pushbutton                                  | 91.5    | 3.58     |
| Latching mushroom head Emergency stop pushbutton with key | 115     | 4.53     |
| Key switch                                                | 105.5   | 4.15     |