# Product datasheet Characteristics

## **XAPA1104H2**

empty control station - XAP-A - plastic - 4 openings in 2 columns - H2

Price\*: 53.82 GBP



Harmony XAP  Empty control station without hinges  XAPA  For Ø 30.5 mm control and signalling units	
XAPA	100 I
For Ø 30.5 mm control and signalling units	
5 5	<del>ن</del> غ
85 x 146 mm	
83 mm	
4 cut-outs	, see
Grey	<u>}</u>
Grey	<u> </u>
Glass reinforced polyester	
Undrilled	: <u>:</u>
Flush	
IP65 conforming to IEC 60529 IP69 conforming to NF C 20-010 IP69K	or determining
High resistant to acids High resistant to all solvents High resistant to bases High resistant to diesel High resistant to mineral salts High resistant to oils and greases High resistant to petrol High resistant to sea water	in for and is not to be used to
	83 mm  4 cut-outs  Grey  Grey  Glass reinforced polyester  Undrilled  Flush  IP65 conforming to IEC 60529 IP69 conforming to NF C 20-010 IP69K  High resistant to acids High resistant to bases High resistant to diesel High resistant to mineral salts High resistant to oils and greases High resistant to petrol

#### Complementary

Number of vertical rows	2	
Flame retardance	M3 conforming to CSTB VO conforming to UL 94	
Product weight	0.47 kg	.ie

#### Environment

LITVITOTITICITE		
Protective treatment	TC	
	TH	

Ambient air temperature for storage	-4070 °C	
Ambient air temperature for operation	-4070 °C	
Overvoltage category	Class II conforming to IEC 60536 Class II conforming to NF C 20-030	
Fire resistance	850 °C conforming to NF C 20-455 960 °C conforming to IEC 92	

### Contractual warranty

Warranty	18 months
----------	-----------