

Product data sheet

Characteristics

XAPE903

empty flush mounted box - XAP-E - insulated material - without opening - IP 65



Main

Range of product	Harmony XAP
Product or component type	Protective rear cover
Device short name	XAPE
Product destination	For front plate XAPE303
Material	Insulated material
Cable entry	Knock-out cable entries
Product mounting	Flush mounting
IP degree of protection	IP657 conforming to NF C 20-010 IP65 conforming to IEC 60529
Resistance to chemical agents	Good resistant to salts Good resistant to organic acids Good resistant to oils and petrol Good resistant to diluted mineral acids Good resistant to chloride and fluoride solvents Good resistant to alcohols Good resistant to acetone

Complementary


Product weight	0.06 kg
----------------	---------

Environment

Protective treatment	TC TH
Ambient air temperature for storage	-40...70 °C
Ambient air temperature for operation	-25...70 °C
Class of protection against electric shock	Class I conforming to NF C 20-030 Class I conforming to IEC 60536

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Dimensions and Mounting



P Usable depth

b		P	
mm	in.	mm	in.
118	4.65	82.5	3.25