# Product data sheet Characteristics

## XAPM4508H29

die-cast empty control station - XAPM - Ø 22 zinc alloy - 8 openings

M	ai	n

Range of product	Harmony XAP		
Product or component type	Die-cast empty control station		
Device short name	XAPM		
Product destination	For Ø 22 mm control and signalling units		
Product front plate size	80 x 220 mm		
Usable depth	74.5 mm		
Number of cut-out	8 cut-outs		
Colour of base of enclosure	Blue		
Colour of cover	Blue		
Material	Zinc alloy		
Cable entry	1 hole without blanking plug for ISO 429248 cable gland 25 mm		
Product mounting	Flush mounting		
IP degree of protection IP657 conforming to NF C 20-010 IP65 conforming to IEC 60529			

### Complementary


Number of vertical rows	2	
Product weight	1.37 kg	

#### Environment

Protective treatment	TC				
Ambient air temperature for storage	-4070 °C				
Ambient air temperature for operation	-2570 °C				
Class of protection against electric shock	Class I conforming to NF C 20-030 Class I conforming to IEC 60536				

## XAPM4508H29

### **Dimensions and Fixing**



- (1) 1 hole, without blanking plug, for cable gland with 18 mm/0.71 in. maximum clamping capacity
- (3) 2 x Ø 5.6 mm/0.22 in. holes, depth 20 mm/0.78 in.
- P Usable depth

a b			С		G		Н		Р		
mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.
80	3.15	220	6.89	77	3.03	50	1.97	205	8.07	74.5	2.93

Refer to the product characteristics to get the number of cut-outs.

Cut-out interaxis dimensions (vertical mounting)



- b1 Vertical interaxis: 40 mm/1.57 in.
- b2 Horizontal interaxis: 30 mm/1.18 in.