

# XB6DA25B

black rectangular flush complete pushbutton Ø16  
spring return 1NO+1NC unmarked



Price\* : 11.94 GBP



## Main

|                               |                                                  |
|-------------------------------|--------------------------------------------------|
| Range of product              | Harmony XB6                                      |
| Product or component type     | Complete push-button                             |
| Device short name             | XB6                                              |
| Bezel material                | Plastic                                          |
| Mounting diameter             | 16 mm                                            |
| Sale per indivisible quantity | 1                                                |
| Shape of signaling unit head  | Rectangular                                      |
| Type of operator              | spring return                                    |
| Operator profile              | Black flush, unmarked                            |
| Contacts type and composition | 1 NO + 1 NC                                      |
| Contact operation             | Slow-break                                       |
| Connections - terminals       | Faston connectors, connection size: 2.8 x 0.5 mm |

## Complementary

|                               |                                                                                                     |
|-------------------------------|-----------------------------------------------------------------------------------------------------|
| CAD overall width             | 24 mm                                                                                               |
| CAD overall height            | 18 mm                                                                                               |
| CAD overall depth             | 57 mm                                                                                               |
| Terminals description ISO n°1 | (13-14)NO<br>(21-22)NC                                                                              |
| Product weight                | 0.022 kg                                                                                            |
| Operating position            | Any position                                                                                        |
| Positive opening              | With conforming to EN/IEC 60947-5-1 appendix K                                                      |
| Operating travel              | 1 mm (NO changing electrical state)<br>2 mm (NC changing electrical state)<br>3.5 mm (total travel) |
| Operating force               | 3.5 N NO changing electrical state<br>4.5 N NC changing electrical state                            |
| Mechanical durability         | 2000000 cycles                                                                                      |

|                                        |                                                                                                                                                                                                                                                     |
|----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Contacts material                      | Silver alloy (Ag/Ni)                                                                                                                                                                                                                                |
| Short-circuit protection               | 6 A cartridge fuse type gG                                                                                                                                                                                                                          |
| [Ui] rated insulation voltage          | 250 V (pollution degree 3) conforming to EN/IEC 60947-1                                                                                                                                                                                             |
| [Uimp] rated impulse withstand voltage | EN/IEC 60947-1 4 kV                                                                                                                                                                                                                                 |
| [Ie] rated operational current         | 3 A at 120 V, AC-15, B300 conforming to EN/IEC 60947-5-1<br>1.5 A at 240 V, AC-15, B300 conforming to EN/IEC 60947-5-1<br>0.1 A at 250 V, DC-13, R300 conforming to EN/IEC 60947-5-1<br>0.22 A at 125 V, DC-13, R300 conforming to EN/IEC 60947-5-1 |
| Electrical durability                  | 1000000 cycles, AC-15 at 230 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C<br>1000000 cycles, DC-13 at 230 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C    |
| Electrical reliability                 | $\Lambda = 10\exp(-8)$ at 5 V and 1 mA with confidence level of 90 % conforming to IEC 60947-5-4                                                                                                                                                    |

## Environment

|                                       |                                                                                                                                                                                                                    |
|---------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Protective treatment                  | TC                                                                                                                                                                                                                 |
| Ambient air temperature for storage   | -40...70 °C                                                                                                                                                                                                        |
| Ambient air temperature for operation | -25...70 °C                                                                                                                                                                                                        |
| Electrical shock protection class     | Class II conforming to IEC 61140                                                                                                                                                                                   |
| IP degree of protection               | IP65 conforming to IEC 60529                                                                                                                                                                                       |
| NEMA degree of protection             | NEMA 13 conforming to UL 50<br>NEMA 4 conforming to UL 50<br>NEMA 4X conforming to UL 50<br>NEMA 13 conforming to CSA C22.2 No 94<br>NEMA 4 conforming to CSA C22.2 No 94<br>NEMA 4X conforming to CSA C22.2 No 94 |
| Standards                             | JIS C 4520<br>UL 508<br>JIS C 852<br>EN/IEC 60947-5-1<br>EN/IEC 60947-1<br>EN/IEC 60947-5-5<br>CSA C22.2 No 14                                                                                                     |
| Product certifications                | UL<br>CCC<br>CSA<br>GOST                                                                                                                                                                                           |
| Vibration resistance                  | +/- 3 mm (f= 2...500 Hz) conforming to IEC 60068-2-6<br>5 gn (f= 2...500 Hz) conforming to IEC 60068-2-6                                                                                                           |
| Shock resistance                      | 30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC 60068-2-27<br>50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC 60068-2-27                                     |

## Offer Sustainability

|                            |                                                                                                                             |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                       |
| REACH free of SVHC         | Yes                                                                                                                         |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a>                           |
| Toxic heavy metal free     | Yes                                                                                                                         |
| Mercury free               | Yes                                                                                                                         |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                         |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a>                                                                                      |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                               |
| Circularity Profile        | <a href="#">End of Life Information</a>                                                                                     |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|