

# XB7ND25

selector switch - Ø 22 - black - standard handle  
- 2 positions - 1 NO + 1NC



## Main

|                               |                                                                                       |
|-------------------------------|---------------------------------------------------------------------------------------|
| Range of product              | Harmony XB7                                                                           |
| Product or component type     | Monolithic selector switch                                                            |
| Device short name             | XB7                                                                                   |
| Mounting diameter             | 22 mm                                                                                 |
| Sale per indivisible quantity | 10                                                                                    |
| Product weight                | 0.026 kg                                                                              |
| IP degree of protection       | IP65 (front face) conforming to IEC 60529<br>IP20 (rear face) conforming to IEC 60529 |
| Shape of signaling unit head  | Round                                                                                 |
| Type of operator              | Stay put                                                                              |
| Operator profile              | Black                                                                                 |
| Operator position information | 2 positions 90°                                                                       |
| Contacts type and composition | 1 NO + 1 NC                                                                           |
| Positive opening              | With positive opening conforming to EN/IEC 60947-5-1 appendix K                       |

## Complementary

|                                        |                                                                                                                                                                                                                                                                                  |
|----------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CAD overall width                      | 29 mm                                                                                                                                                                                                                                                                            |
| CAD overall height                     | 29 mm                                                                                                                                                                                                                                                                            |
| CAD overall depth                      | 68.5 mm                                                                                                                                                                                                                                                                          |
| Terminals description ISO n°1          | (13-14)NO<br>(21-22)NC                                                                                                                                                                                                                                                           |
| Device mounting                        | Fixing hole: Ø 22.5 mm (22.3 +0.4/0) conforming to EN/IEC 60947-1                                                                                                                                                                                                                |
| Fixing center                          | >= 30 x 40 mm on support panel, plastic, thickness: 2...6 mm<br>>= 30 x 40 mm on support panel, metal, thickness: 1...6 mm                                                                                                                                                       |
| Fixing mode                            | Fixing nut recommended torque: 2.2 N.m (+/- 0.2 N.m)                                                                                                                                                                                                                             |
| Contacts operation                     | Slow-break                                                                                                                                                                                                                                                                       |
| Mechanical durability                  | 300000 cycles                                                                                                                                                                                                                                                                    |
| Connections - terminals                | Screw clamp terminals: 1 x 0.34...2 x 2.5 mm² without cable end conforming to EN/IEC 60947-1<br>Screw clamp terminals: <= 2 x 1.5 mm² with cable end conforming to EN/IEC 60947-1                                                                                                |
| Tightening torque                      | 0.8...1.2 N.m conforming to EN 60947-1                                                                                                                                                                                                                                           |
| Shape of screw head                    | Slotted head compatible with flat Ø 5.5 mm screwdriver<br>Slotted head compatible with flat Ø 4 mm screwdriver<br>Cross head compatible with pozidriv No 1 screwdriver<br>Cross head compatible with Philips no 1 screwdriver<br>Cross head compatible with JIS No 1 screwdriver |
| Short circuit protection               | 4 A cartridge fuse type gG conforming to EN/IEC 60947-5-1                                                                                                                                                                                                                        |
| [Ui] rated insulation voltage          | 250 V (degree of pollution: 3) conforming to EN/IEC 60947-1                                                                                                                                                                                                                      |
| [Uimp] rated impulse withstand voltage | 4 kV conforming to EN/IEC 60947-1                                                                                                                                                                                                                                                |
| [Ie] rated operational current         | 0.6 A at 120 V, AC-14, D300 conforming to EN/IEC 60947-5-1<br>0.3 A at 240 V, AC-14, D300 conforming to EN/IEC 60947-5-1<br>0.22 A at 125 V, DC-13, R300 conforming to EN/IEC 60947-5-1<br>0.1 A at 250 V, DC-13, R300 conforming to EN/IEC 60947-5-1                            |
| Electrical reliability IEC 60947-5-4   | $\Lambda < 10\exp(-6)$ at 17 V, 5 mA conforming to IEC 60947-5-4                                                                                                                                                                                                                 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the Schneider Electric group. It is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment


|                                            |                                                                                                                                                                                |
|--------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Protective treatment                       | TH                                                                                                                                                                             |
| Ambient air temperature for storage        | -40...70 °C                                                                                                                                                                    |
| Ambient air temperature for operation      | -25...70 °C                                                                                                                                                                    |
| Class of protection against electric shock | Class II conforming to IEC 61140                                                                                                                                               |
| NEMA degree of protection                  | NEMA 3 conforming to UL 50 E<br>NEMA 12 conforming to UL 50 E                                                                                                                  |
| Standards                                  | EN/IEC 60947-1<br>EN/IEC 60947-5-1<br>JIS C 4520<br>UL 508<br>CSA C22.2 No 14                                                                                                  |
| Vibration resistance                       | 5 gn (f = 2...500 Hz) conforming to IEC 60068-2-6                                                                                                                              |
| Shock resistance                           | 30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC 60068-2-27<br>50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC 60068-2-27 |

---

Selector Switch, Standard Handle

---

Dimensions



e Support panel thickness: 1 to 6 mm/0.4 to 0.24 in. (metal), 2 to 6 mm/0.8 to 0.24 in. (plastic).

## Mounting

### Diameter of Finished Fixing Holes



- (1) Minimum value.
- (2) 40 mm/1.58 in. for Emergency switching off pushbutton only.
- (3) Standard value: Ø 22.3 (0; + 0.4) mm/Ø 0.88 (0; + 0.02) in.

### "U" Type Tag Connection



- (1) 6.5 mm/0.26 in. recommended, 7 mm/0.28 in. max.
- (2) M3 screw clamp terminal.

---

Wiring

---

