Product data sheet Characteristics

XBKH70000002M

hour counter - mechanical 7 digit display - 230 V AC



Main Range of product Zelio Count Product or component type Display type Mechanical Size 48 x 48 mm Display digits 7 digit(s) Reset Without

Electromechanical

Complementary

Complementary		
[Us] rated supply voltage	230 V AC (Us +/- 10 %) at 50 Hz	
Power consumption	1 VA	
Backup time	Permanent	
Counting mode	Adding 1/100 of an hour	
Time range	099 999.99 h	
Input function	Enable	
Input type	Contact	
Mounting mode	Flush-mounted	
Mounting support	Panel mounting	
Fixing mode	By self-locking clamp	
Connections - terminals	Screw terminal block	
Height	48 mm	
Product weight	0.06 kg	
Width	48 mm	
Character size	5 mm	
CAD overall width	48 mm	
CAD overall height	48 mm	
CAD overall depth	63 mm	

Technology type

Environment


Standards	EN/IEC 50081-2	
	EN/IEC 50082-2	
	VDE 0435	
Product certifications	UR	
Ambient air temperature for operation	-1050 °C	
Ambient air temperature for storage	-2570 °C	
Vibration resistance	3 gn (f = 10150 Hz) conforming to EN/IEC 60068-2-6	
Shock resistance	30 gn for 11 ms conforming to EN/IEC 60068-2-27	
Class of protection against electric shock	Class II conforming to EN/IEC 60536	

XBKH70000002M


Electromechanical and Electronic Totalizing Timers

Timers with Mechanical Display

XBKH7000000•M




Flush-Mounting



Timers with LCD Display

XBKH81000033E



Flush-Mounting

in. 1.77-0.004