



Main

| | |
|-------------------------------|-----------------------------|
| Range of product | OsiSense XC |
| Series name | Standard format |
| Product or component type | Limit switch |
| Device short name | XCMN |
| Sensor design | Miniature |
| Body type | Fixed |
| Head type | Multi-directional head |
| Material | Plastic |
| Fixing mode | By the body |
| Movement of operating head | Multi-directional |
| Type of operator | Spring return cat's whisker |
| Switch actuation | By any moving part |
| Electrical connection | Fixed cable |
| Cable length | 1 m |
| Number of poles | 2 |
| Contacts type and composition | 1 NO + 1 NC |
| Contacts operation | Snap action |
| Positive opening | Without |
| Minimum force for tripping | 0.1 N |
| Maximum actuation speed | 1 m/s |

Complementary

| | |
|--|---|
| Body material | Plastic |
| Head material | Zamak |
| Type of approach | Multi-directional approach |
| Cable composition | 4 x 0.75 mm ² |
| Wire insulation material | PvR |
| Contacts insulation form | Zb |
| Contact code designation | B300 , AC-15 (Ue = 240 V , Ie = 1.5 A) conforming to EN/IEC 60947-5-1 appendix A R300 , DC-13 (Ue = 250 V , Ie = 0.1 A) conforming to EN/IEC 60947-5-1 appendix A |
| [Ui] rated insulation voltage | 300 V degree of pollution 3 conforming to UL 508 300 V degree of pollution 3 conforming to CSA C22-2 No 14 400 V degree of pollution 3 conforming to IEC 60947-5-1 |
| Resistance across terminals | ≤ 25 mOhm conforming to IEC 60255-7 category 3 |
| [Uimp] rated impulse withstand voltage | 4 kV conforming to IEC 60664 4 kV conforming to IEC 60947-1 |
| Short circuit protection | 6 A by gG cartridge fuse |
| Electrical durability | 5000000 cycles , DC-13 , 24 V , 3 W , load factor: 0.5 , operating rate: ≤ 60 cyc/mn 5000000 cycles , DC-13 , 48 V , 2 W , load factor: 0.5 , operating rate: ≤ 60 cyc/mn 5000000 cycles , DC-13 , 120 V , 1 W , load factor: 0.5 , operating rate: ≤ 60 cyc/mn |
| Mechanical durability | 5000000 cycles |
| Width | 30 mm |

| | |
|----------------|---------|
| Height | 182 mm |
| Depth | 16 mm |
| Product weight | 0.08 kg |

Environment

| | |
|--|--|
| Shock resistance | 25 gn (duration = 18 ms) conforming to IEC 60068-2-27 |
| Vibration resistance | 5 gn (f = 10...500 Hz) conforming to IEC 60068-2-6 |
| IP degree of protection | IP65 conforming to IEC 60529 |
| IK degree of protection | IK04 conforming to EN 50102 |
| Class of protection against electric shock | Class II conforming to NF C 20-030 Class II conforming to IEC 61140 |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -40...70 °C |
| Protective treatment | TC |
| Product certifications | CCC CSA UL |
| Standards | CSA C22-2 No 14 EN/IEC 60204-1 EN/IEC 60947-5-1 UL 508 |
| RoHS EUR conformity date | 4Q2009 |
| RoHS EUR status | Will be compliant |