



## Main

|                               |                               |
|-------------------------------|-------------------------------|
| Range of product              | Preventa Safety detection     |
| Product or component type     | Safety switch                 |
| Component name                | XCSMP                         |
| Design                        | Miniature                     |
| Material                      | Plastic                       |
| Head type                     | Key operated fixed head       |
| Contacts type and composition | 2 NC + 1 NO                   |
| Contacts operation            | Slow-break, break before make |
| Electrical connection         | Pre-cabled                    |
| Number of poles               | 3                             |
| Locking options description   | Without locking of actuator   |

## Complementary

|  |   |
|--|---|
| Insulation                                   | Double insulated  |
| Cable length                                 | 2 m   |
| Cable composition                            | 6 x 0.5 mm <sup>2</sup>   |
| Mechanical durability                        | >= 1000000 cycles   |
| Minimum actuation speed                      | 0.05 m/s  |
| Maximum actuation speed                      | 1.5 m/s   |
| [Ie] rated operational current               | 1.5 A at 120 V utilisation category AC-15, C300 conforming to EN/IEC 60947-5-1<br>0.75 A at 240 V utilisation category AC-15, C300 conforming to EN/IEC 60947-5-1<br>0.27 A at 250 V utilisation category DC-13, Q300 conforming to EN/IEC 60947-5-1<br>0.55 A at 125 V utilisation category DC-13, Q300 conforming to EN/IEC 60947-5-1 |
| [Ithe] conventional enclosed thermal current | 2.5 A   |
| [Ui] rated insulation voltage                | 300 V conforming to CSA C22.2 No 14<br>500 V conforming to EN/IEC 60947-1<br>300 V conforming to UL 508   |
| [Uimp] rated impulse withstand voltage       | 6 kV conforming to EN/IEC 60947-5-1   |
| Short circuit protection                     | 10 A cartridge fuse type gG (gl)  |
| Actutr forcible withdrawal rtc               | 8 N   |
| Actuator force for extraction                | >= 8 N  |
| Operating rate                               | 20 cyc/mn for maximum durability  |
| Safety level                                 | Can reach SIL 3 with the appropriate monitoring system and correctly wired conforming to EN/IEC 61508<br>Can reach PL = e with the appropriate monitoring system and correctly wired conforming to EN/ISO 13849-1<br>Can reach category 4 with the appropriate monitoring system and correctly wired conforming to EN/ISO 13849-1       |
| Safety reliability data                      | B10d = 5000000 (value given for a life time of 20 years limited by mechanical or contact wear)  |
| Body material                                | PA (polyamide)  |
| Head material                                | PA (polyamide)  |
| Depth  | 30 mm   |
| Height                                       | 87 mm   |
| Width  | 15 mm   |
| Product weight                               | 0.11 kg   |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

|  |  |
|--|--|
| Standards                                  | EN 1088/ISO 14119<br>EN/IEC 60204-1<br>EN/IEC 60947-5-1<br>EN/ISO 12100<br>UL 508<br>CSA C22.2 No 14 |
| Product certifications                     | CSA<br>CUL<br>UL   |
| Protective treatment                       | TC   |
| Ambient air temperature for operation      | -25...70 °C  |
| Ambient air temperature for storage        | -25...80 °C  |
| Vibration resistance                       | 6 gn (f = 10...55 Hz) conforming to IEC 60068-2-6  |
| Shock resistance                           | 50 gn for 11 ms conforming to IEC 60068-2-27   |
| Class of protection against electric shock | Class II conforming to EN/IEC 60536  |
| IP degree of protection                    | IP67 conforming to EN/IEC 60529 and EN/IEC 60947-5-1   |

## Offer Sustainability

|                          |   |
|--------------------------|---|
| Sustainable offer status | Not Green Premium product   |
| RoHS (date code: YYWW)   | Compliant - since 0642 - <a href="#">Schneider Electric declaration of conformity</a> |

## Contractual warranty

|        |           |
|--------|-----------|
| Period | 18 months |
|--------|-----------|