



Main

Range of product Harmony XAC

Product or component type Contact block

Component name XENT

Electrical circuit type Control circuit
Power circuit

Contact block application Emergency stop push-button

Contact block type Single

Type of operator Spring return

Product compatibility XACB

Contacts type and composition 3 NC

Contact operation Slow-break

Complementary

Connections - terminals Screw clamp terminals, 1 x 2.5 mm² with or without cable end
Screw clamp terminals, 2 x 1.5 mm² with or without cable end

Mechanical durability 3000000 cycles

[I]the] conventional enclosed thermal current 10 A

[Ui] rated insulation voltage 400 V (pollution degree 3) conforming to IEC 60947-1

[Uimp] rated impulse withstand voltage IEC 60947-1 4 kV

Short-circuit protection 6 A fuse protection by cartridge fuse type aM

Rated operational power in W 3000 W AC-23B at 400 V

Terminals description ISO n°1
(31-32)NC
(11-12)NC
(21-22)NC

Product weight 0.04 kg

Environment

Standards CSA C22.2 No 14
EN/IEC 60947-5-1
UL 508

Ambient air temperature for operation -25...70 °C

Ambient air temperature for storage -40...70 °C

Vibration resistance	15 gn (f= 10...500 Hz) conforming to IEC 60068-2-6
Shock resistance	70 gn conforming to IEC 60068-2-27
Overvoltage category	Class II conforming to IEC 61140

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------