



Main

Range of product	XR and XF
Product or component type	Overtravel limit switches
Device short name	XF9
Electrical circuit type	Power circuit
Product specific application	Safety of hoisting equipment
Material	Aluminium alloy: case
Type of operator	Manual latching, restricted by a padlockable device
Number of poles	4
[Ie] rated operational current	, Ie = 130 A 2-pole scheme AC-3, Ie = 65 A 3-pole scheme

Complementary

Reset	Manual reset
Switch actuation	Horizontal approach
Maximum displacement angle	75 °
Contacts type and composition	Without auxiliary contact block
Contact operation	Snap action
[Ith] conventional enclosed thermal current	160 A at -25...40 °C 2-pole scheme 80 A at -25...40 °C 3-pole scheme
[Ui] rated insulation voltage	500 V conforming to IEC 158-1 500 V conforming to IEC 947-4 500 V conforming to VDE 0110 group C 600 V conforming to CSA C22.2 No 14
Rated breaking capacity	1000 kA at 500 V 2-pole scheme conforming to IEC 158-1 630 kA at 660 V 2-pole scheme conforming to IEC 158-1
Cable cross section	1 flexible cable 2.5...16 mm ² with cable end 1 flexible cable 2.5...25 mm ² without cable end 1 solid cable 2.5...25 mm ² without cable end 2 flexible cable 2.5...16 mm ² without cable end 2 flexible cable 2.5...6 mm ² with cable end 2 solid cable 4...16 mm ² without cable end
Cable entry	3 entries tapped for Pg 29 cable gland
Product weight	3.83 kg

Environment

Standards	VDE 0660 IEC 947-4 IEC 947-1 IEC 158-1 NF C 63-110
Product certifications	CSA
Protective treatment	TC
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C
IP degree of protection	IP54 conforming to EN/IEC 60529

Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope
-------------------	--------------------------------------------

Contractual warranty

Warranty	18 months
----------	-----------