



Main

Product or component type	Controllers separate parts
Accessory / separate part category	Control accessory
Product specific application	Light hoisting applications
Product compatibility	XKB
Accessory / separate part type	Contact block
Accessory / separate part specific characteristic	For use with zero (center) position interlocking handle

Complementary

Contact block per direction [control circuit]	4 per movement 1 zero (center) position
Electrical connection	Screw clamp terminal, clamping capacity: 1 x 0.5...1 x 1.5 mm ² Screw clamp terminal, clamping capacity: 1 x 0.5...1 x 2.5 mm ²
Enclosure/Cubicle description	Monobloc
Contacts type and composition	1 NO 8 NO
Contact operation	Slow-break Double-break
[Ith] conventional free air thermal current	10 A conforming to IEC 337-1 10 A conforming to NF C 63-140 10 A conforming to VDE 0660 10 A conforming to CSA C22.2 No 14
[Ui] rated insulation voltage	500 V AC/DC conforming to IEC 158-1 500 V AC/DC conforming to NF C 20-040 500 V AC/DC conforming to VDE 0110
Maximum resistance across terminals	25 mOhm at 1 A conforming to NF C 93-050 25 mOhm conforming to NF C 93-050
Positive opening	With Without
Short-circuit protection	10 A cartridge fuse type gG conforming to IEC 337-1B 10 A cartridge fuse type gG conforming to VDE 0660 part 2
Electrical durability	1000000 cycles DC inductive load at 120 V, power broken = 75 conforming to IEC 337-1 DC-11, operating rate <60 cyc/mn 0.5 1000000 cycles DC inductive load at 24 V, power broken = 90 conforming to IEC 337-1 DC-11, operating rate <60 cyc/mn 0.5

1000000 cycles DC inductive load at 48 V, power broken = 90 conforming to IEC 337-1 DC-11, operating rate <60 cyc/mn 0.5

Product weight	0.215 kg
----------------	----------

Environment

Standards	CENELEC EN 50013
-----------	------------------

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
-------------------	---

Mercury free	Yes
--------------	-----

RoHS exemption information	Yes
----------------------------	---------------------

China RoHS Regulation	China RoHS declaration
-----------------------	--

WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
------	---

Contractual warranty

Warranty	18 months
----------	-----------