Product datasheet Characteristics

XKDZ1547

potentiometer - 4700 Ohm - 15 mm - for XKD

Price*: 503.17 GBP



Main
Produc

Product or component type	Controllers separate parts
Accessory / separate part category	Control accessories
Product specific application	Medium hoisting applications Heavy hoisting applications
Product compatibility	XKM XKD
Accessory / separate part type	Potentiometer
Condition of use	For applications requiring an extended neutral zone
Ohmic value	4700 Ohm
Size	15 mm
Complementary	
Standards	UTE 93-265
Potentiometer characteristic	Continuous rotational operation Linear function
Operating angle	360 °
Mechanical durability	3000000 cycles
Centre tap	Wired out to terminal
Centre tap dead zone	30 °
Power dissipation in W	3 W 85 °C
Connections - terminals	Flying leads from soldered standard tags
Product weight	0.055 kg
Environment	
Mounting mode	By the body
Offer Sustainability	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China RoHS Regulation	China RoHS declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Complementary

Standards	UTE 93-265	
Potentiometer characteristic	Continuous rotational operation Linear function	e in
Operating angle	360 °	Ţ
Mechanical durability	3000000 cycles	9
Centre tap	Wired out to terminal	9
Centre tap dead zone	30 °	
Power dissipation in W	3 W 85 °C	
Connections - terminals	Flying leads from soldered standard tags	<u> </u>
Product weight	0.055 kg	<u> </u>

Environment

	5	
Mounting mode	By the hody	
Mounting mode	Dy the body	
•	• •	

Offer Sustainability

onor odotamasmity		
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
China RoHS Regulation	China RoHS declaration	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

Warranty 18 months