



### Main

|   |  |
|---|--|
| Range of product                        | OsiSense XM  |
| Product or component type               | Electronic pressure sensors  |
| Pressure sensor type                    | Pressure transmitter   |
| Pressure switch type of operation       | Pressure switch with 2 switching outputs   |
| Device short name                       | XMLR   |
| Pressure sensor size                    | 36 psi<br>2.5 bar<br>250 kPa   |
| Maximum permissible accidental pressure | 174 psi<br>1200 kPa<br>12 bar  |
| Destruction pressure                    | 12 bar<br>174 psi<br>1200 kPa  |
| Controlled fluid                        | Fresh water (0...80 °C)<br>Air (-20...80 °C)<br>Hydraulic oil (-20...80 °C)<br>Refrigeration fluid (-20...80 °C) |
| Fluid connection type                   | G 1/4 (female) conforming to DIN 3852-Y  |
| [Us] rated supply voltage               | 24 V DC SELV (voltage limits: 17...33 V)   |

### Complementary

|  |   |
|--|---|
| Current consumption                                    | <= 50 mA  |
| Electrical connection                                  | Male connector M12, 4 pins                      |
| Type of output signal                                  | Discrete  |
| Discrete output type                                   | Solid state NPN, 2 NO/NC programmable           |
| Maximum switching current                              | 250 mA  |
| Contacts type and composition                          | 2 NO/NC programmable                            |
| Scale type   | Fixed differential                              |
| Maximum voltage drop                                   | 2 V   |
| Adjustable range of switching point on rising pressure | 20...250 kPa<br>2.9...36.2 psi<br>0.2...2.5 bar |

|   |   |
|---|---|
| Adjustable range of switching point on falling pressure | 13...242 kPa<br>1.81...35.2 psi<br>0.13...2.42 bar  |
| Minimum differential travel                             | 0.08 bar<br>1.1 psi<br>8 kPa  |
| Materials in contact with fluid                         | 316L stainless steel<br>Ceramic<br>Fluorocarbon FKM (Viton)   |
| Front material  | Polyester   |
| Housing material  | 316L stainless steel<br>Polyacrylamide  |
| Operating position                                      | Any position, but disposals can falsified the measurement in case of upside down mounting   |
| Protection type   | Short-circuit protection<br>Overload protection<br>Overvoltage protection<br>Reverse polarity   |
| Response time on output                                 | <= 5 ms for discrete output   |
| Switching output time delay                             | 0...50 s in steps of 1 second   |
| Display type  | 4 digits 7 segments   |
| Local signalling  | 2 LEDs (yellow)light ON when switch is actuated:  |
| Display response time type                              | Fast 50 ms<br>Normal 200 ms<br>Slow 600 ms  |
| Maximum delay first up                                  | 300 ms  |
| Overall accuracy  | <= 1 % of the measuring range   |
| Measurement accuracy on switching output                | <= 0.6 % of the measuring range   |
| Repeat accuracy   | <= 0.2 % of the measuring range   |
| Drift of the sensitivity                                | +/- 0.03 % of measuring range/°C  |
| Drift of the zero point                                 | +/- 0.1 % of measuring range/°C   |
| Display accuracy  | <= 1 % of the measuring range   |
| Mechanical durability                                   | 10000000 cycles   |
| Depth   | 42 mm   |
| Height  | 93 mm   |
| Width   | 41 mm   |
| Product weight  | 0.19 kg   |
| [Uimp] rated impulse withstand voltage                  | 0.5 kV DC   |
| Electromagnetic compatibility                           | Susceptibility to electromagnetic fields: 10 V/m 80...2000 MHz conforming to EN/IEC 61000-4-3<br>Immunity to conducted RF disturbances: 10 V 0.15...80 MHz conforming to EN/IEC 61000-4-6<br>Surge immunity test: 1 kV conforming to EN/IEC 61000-4-5<br>Electrical fast transient/burst immunity test: 2 kV conforming to EN/IEC 61000-4-4<br>Electrostatic discharge immunity test: 8 kV air, 4 kV contact conforming to EN/IEC 61000-4-2 |

## Environment

|                                       |  |
|---------------------------------------|--|
| Marking                               | CE   |
| Product certifications                | EAC<br>CULus   |
| Standards                             | EN/IEC 61326-2-3<br>UL 61010-1                                     |
| Ambient air temperature for operation | -20...80 °C  |
| Ambient air temperature for storage   | -40...80 °C  |
| IP degree of protection               | IP65 conforming to EN/IEC 60529<br>IP67 conforming to EN/IEC 60529 |
| Vibration resistance                  | 20 gn (f= 10...2000 Hz) conforming to EN/IEC 60068-2-6             |
| Shock resistance                      | 50 gn conforming to EN/IEC 60068-2-27                              |

### Offer Sustainability

|                            |   |
|----------------------------|---|
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Dimensions




(1) Fluid entry: G 1/4 A female

---

Connections and Schema

---

Connector Wiring



---

Switching Output Description. Hysteresis Mode

---

The hysteresis switching mode is typically used for the “pumping and/or emptying applications”.



X : Time  
Y : Pressure  
(1) : Output  
NP : Nominal Pressure  
SP : Set point (adjustable from 8 % to 100 % NP)  
rP : Reset point (adjustable from 5 % to 97 % NP)

Switching Output Description. Window Mode

The window switching mode is typically used for the “pressure regulation applications”



- X : Time
- Y : Pressure
- (1) Output
- NP : Nominal pressure
- FH : High switching point (adjustable from 8 % to 100 % NP)
- FL : Low switching point (adjustable from 5 % to 97 % NP)

Switching Output Description. Time Delay

The Time Delay is typically used to filter out the fast pressure transients.  
The output only switches after a time “dS” and “dr” adjustable from 0 to 50 seconds.



- X : Time
- Y : Pressure
- (1) Output
- SP : Set point
- rP : Reset point
- dS : Time delay on the set point
- dr : Time delay on the reset point