



Price\* : 121.51 GBP



## Main

|                                    |                                         |
|------------------------------------|-----------------------------------------|
| Range of product                   | OsiSense XS                             |
| Series name                        | Application                             |
| Sensor type                        | Inductive proximity sensor              |
| Device application                 | Rotation monitoring                     |
| Sensor name                        | XSA                                     |
| Sensor design                      | Cylindrical M30                         |
| Size                               | 81 mm                                   |
| Body type                          | Fixed                                   |
| Detector flush mounting acceptance | Flush mountable                         |
| Material                           | Metal                                   |
| Enclosure material                 | Nickel plated brass                     |
| Type of output signal              | Discrete                                |
| Wiring technique                   | 2-wire                                  |
| [Sn] nominal sensing distance      | 10 mm                                   |
| Discrete output function           | 1 NC                                    |
| Output circuit type                | AC/DC                                   |
| Electrical connection              | Cable                                   |
| Cable length                       | 2 m                                     |
| [Us] rated supply voltage          | 24...210 V DC<br>24...240 V AC 50/60 Hz |
| Switching capacity in mA           | 5...200 mA DC<br>5...350 mA AC          |
| IP degree of protection            | IP67 conforming to IEC 60529            |

## Complementary

|                |           |
|----------------|-----------|
| Thread type    | M30 x 1.5 |
| Detection face | Frontal   |

|                            |                           |
|----------------------------|---------------------------|
| Front material             | PPS                       |
| Adjustable frequency range | 6...150 cyc/mn            |
| Operating zone             | 0...8 mm                  |
| Differential travel        | 3...15% of Fr             |
| Repeat accuracy            | 3% of Sr                  |
| Cable composition          | 2 x 0.34 mm <sup>2</sup>  |
| Wire insulation material   | PvR                       |
| Status LED                 | Output state: 1 LED (red) |
| Supply voltage limits      | 20...264 V AC/DC          |
| Maximum residual current   | 1.5 mA open state         |
| Switching frequency        | <= 100 Hz                 |
| Maximum voltage drop       | <5.7 V (closed)           |
| Run-up delay at power-up   | 9 s standard              |
| Marking                    | CE                        |
| Threaded length            | 57 mm                     |
| Height                     | 30 mm                     |
| Length                     | 81 mm                     |
| Product weight             | 0.3 kg                    |

## Environment

|                                       |                  |
|---------------------------------------|------------------|
| Product certifications                | CCC<br>UL<br>CSA |
| Ambient air temperature for operation | -25...70 °C      |
| Ambient air temperature for storage   | -40...85 °C      |

## Offer Sustainability

|                            |                                                                                                   |
|----------------------------|---------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                             |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes                                                                                               |
| RoHS exemption information | <a href="#">Yes</a>                                                                               |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                     |
| Circularity Profile        | <a href="#">End of Life Information</a>                                                           |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|