



Price\* : 171.04 GBP



⚠ Discontinued

### Main

Range of product	OsiSense XS
Series name	General purpose
Sensor type	Inductive proximity sensor
Product specific application	-
Sensor name	XSD
Sensor design	Form 80 x 80 x 40
Size	40 mm
Body type	Fixed
Enclosure material	Plastic
Type of output signal	Discrete
Wiring technique	4-wire
[Sn] nominal sensing distance	40 mm
Discrete output function	1 NO + 1 NC
Discrete output type	PNP
Electrical connection	Screw-clamp terminals
[Us] rated supply voltage	12...48 V DC
IP degree of protection	IP67

### Complementary

Detection face	Frontal
Detector flush mounting acceptance	Non flush mountable
Material	Plastic
Front material	Plastic
Output circuit type	DC
Cable entry	1 entry tapped for 1/2" NPT cable gland
Switching capacity in mA	<= 200 mA
Switching frequency	<= 50 Hz

Marking	CE
Depth	40 mm
Height	100 mm
Width	80 mm

## Environment

Product certifications	CSA UL CCC
Ambient air temperature for operation	-25...70 °C



## Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations <a href="#">End of Life Information</a>

## Contractual warranty


Warranty	18 months
----------	-----------

XSDH407339H7 is replaced by the following group of products:

	<p><b>Inductive sensors XS XS7D1A1PAM12</b> inductive sensor XS7 80x80x26 - PBT - Sn40mm - 12..24VDC - M12 Qty 1</p>
	<p><b>Accessories XSZBD10</b> accessory for sensor - replacement bracket Qty 1</p>

Reason for Substitution: End of life | Substitution date: 30 December 2006

Or XSDH407339H7 may be replaced by any of the following products:

	<p><b>Accessories XZCC12FDM40B</b> female, M12, 4-pin, straight connector - cable gland Pg 7 Qty 1</p>
---	--

Reason for Substitution: End of life | Substitution date: 30 December 2006



### Inductive sensors XS XS7D1A1PAM12DIN

inductive sensor XS7 80x80x26 - PBT - Sn40mm - 12..24VDC - M12

Qty 1

Reason for Substitution: End of life | Substitution date: 30 December 2006

---



### Inductive sensors XS XS7D1A1PBM12DIN

inductive sensor XS7 80x80x26 - PBT - Sn40mm - 12..24VDC - M12

Qty 1

Reason for Substitution: End of life | Substitution date: 30 December 2006

---



### Inductive sensors XS XS7D1A1PBM12

inductive sensor XS7 80x80x26 - PBT - Sn40mm - 12..24VDC - M12

Qty 1

Reason for Substitution: End of life | Substitution date: 30 December 2006

---