

Price* : 69.15 GBP



Main

Range of product	OsiSense XS
Series name	General purpose
Sensor type	Inductive proximity sensor
Product specific application	-
Sensor name	XSE
Sensor design	Form 26 x 26 x 45
Size	45 mm
Body type	Fixed
Enclosure material	Plastic
Type of output signal	Discrete
Wiring technique	2-wire
[Sn] nominal sensing distance	10 mm
Discrete output function	1 NO
Electrical connection	Cable
Cable length	2 m
[Us] rated supply voltage	12...48 V DC
Switching capacity in mA	3...100 mA
IP degree of protection	IP67

Complementary

Detector flush mounting acceptance	Flush mountable
Material	Plastic
Front material	Plastic
Output circuit type	DC
Cable composition	2 x 0.5 mm ²
Wire insulation material	PvR
Supply voltage limits	10...58 V DC
Switching frequency	<= 1000 Hz
Marking	CE
Depth	26 mm
Height	45 mm

Width	26 mm
-------	-------

Environment

Product certifications	CCC
Ambient air temperature for operation	-25...70 °C



Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes

Contractual warranty

Warranty	18 months
----------	-----------

XSEC1071300 is replaced by the following group of products:

	<p>Inductive sensors XS XS7E1A1DAL2</p> <p>inductive sensor XS7 26x26x13 - PBT - Sn10mm - 12..24VDC - cable 2m</p> <p>Qty 1</p>
	<p>Accessories XSZBE10</p> <p>accessory for sensor - replacement bracket</p> <p>Qty 1</p>

Reason for Substitution: End of life | Substitution date: 30 December 2006