



⚠ Discontinued

## Main

Range of product	OsiSense XS
Series name	General purpose
Sensor type	Inductive proximity sensor
Product specific application	-
Sensor name	XSE
Sensor design	Form 26 x 26 x 45
Size	45 mm
Body type	Fixed
Enclosure material	Plastic
Type of output signal	Discrete
Wiring technique	2-wire
[Sn] nominal sensing distance	10 mm
Discrete output function	1 NO
Electrical connection	Remote male connector M12, 4 pins
Cable length	2 m
[Us] rated supply voltage	12...48 V DC
Switching capacity in mA	3...100 mA
IP degree of protection	IP67

## Complementary

Detector flush mounting acceptance	Flush mountable
Material	Plastic
Front material	Plastic
Output circuit type	DC
Supply voltage limits	10...58 V DC
Switching frequency	<= 1000 Hz
Marking	CE
Depth	26 mm
Height	45 mm
Width	26 mm

## Environment

Product certifications	CCC
Ambient air temperature for operation	-25...70 °C



## Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>

## Contractual warranty

Warranty	18 months
----------	-----------

XSEC1071304 is replaced by the following group of products:

	<b>Inductive sensors XS XS7E1A1CAL08M12</b> inductive sensor XS7 26x26x13 - PBT - Sn10mm - 12..24VDC - M12 0.8m Qty 1
	<b>Accessories XSZBE10</b> accessory for sensor - replacement bracket Qty 1

Reason for Substitution: End of life | Substitution date: 30 December 2006