

XUSLDSY5A1560

safety light curtain segments type 4 - XUSLDS
- for hand protection - 1560 mm



Main

Range of product	Preventa Safety detection
Series name	Advanced
Product or component type	Safety light curtain segments type 4
Device short name	XUSLDS
Product specific application	For hand protection
Minimum object diameter for detection	30 mm
Height protected	1560 mm
Number of beams	78

Complementary

Product compatibility	XUSLDM
Detection system	Transmitter-receiver system
Response time	32 ms for two segments 32 ms for three segments 32 ms for four segments
Kit composition	2 sets of 2 brackets with fixings 1 transmitter(s) 1 receiver(s)
Electrical connection	Flying lead with 1 female connector M12 4 pins (transmitter) Flying lead with 1 female connector M12 4 pins (receiver)
Product weight	7.5 kg

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 0806 - Schneider Electric declaration of conformity
Product environmental profile	Available
Product end of life instructions	Available Download End Of Life Manual

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.