



Main

Range of product	Preventa Safety detection
Product or component type	Safety light curtain type 2
Device short name	XUSLN
Design	Compact slim
Detection system	Transmitter-receiver system
Product specific application	For hand protection
Height protected	1350 mm
[Sn] nominal sensing distance	0.3...15 m
Minimum object diameter for detection	30 mm
Type of start	Automatic
Response time	22 ms
Number of beams	63



Complementary

Kit composition	2 sets of 2 brackets with fixings 1 user guide with certificate of conformity 1 transmitter(s) 1 test rod(s) 1 receiver(s) 1 arc suppressor set(s)
[EAA] effective aperture angle	5 ° at 3 m
Light source	GaAIAs LED, 880 nm
[Us] rated supply voltage	24 V DC (+/- 20 %)
[Ie] rated operational current	2 A
Current consumption	50 mA (transmitter) 1.09 A with maximum load (receiver) 90 mA no-load (receiver)
Output type	2 safety outputs OSSD solid-state PNP (NO) (short-circuit protection) 1 alarm output PNP
Output current limits	<= 500 mA
Output voltage	24 V
Output circuit type	DC
Local signalling	4 LEDs (receiver), function: stop, run, top alignment, bottom alignment 2 LEDs (transmitter), function: power supply, diagnostic
Electrical connection	1 male connector M12 5 pins (receiver) 1 male connector M12 4 pins (transmitter)
Function available	Muting possible with external module XPSLCM1150 Monitoring of external switching devices EDM/MPCE LED display of operating modes Alignment aid using 2 LEDs
Marking	CE
Material	Front face : acrylic End caps : 30 % fibre glass impregnated nylon Casing : aluminium
Fixing mode	End brackets
Product weight	4.5 kg

Environment

Standards	IEC 61496-1 IEC 61496-2 (type 2 ESPE) Machinery directive 2006/42/EC EMC 2004/108/EC Work equipment directive 2009/104/EC
Product certifications	CSA TÜV UL
Safety level	Type 2 conforming to IEC 61496-1-2 Can reach PL = c conforming to EN/ISO 13849-1 (correctly wired) Can reach category 2 conforming to EN/ISO 13849-1 (correctly wired)
Safety reliability data	PFH = 2.29E-7 1/h conforming to IEC 61508 (verified in worst case conf: 6 beams), proof test interval = 100 yr
Ambient air temperature for operation	0...55 °C
Ambient air temperature for storage	-25...75 °C
Relative humidity	<= 95 % without condensation
IP degree of protection	IP65
Shock resistance	10 gn for 16 ms conforming to IEC 61496-1
Vibration resistance	0.35 +/- 0.05 mm (f = 10...55 Hz) conforming to IEC 61496-1

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will be Compliant on 3Q2013
Product environmental profile	Available  Download Product Environmental
Product end of life instructions	Available  Download End Of Life Manual