

# XUSLNG5E1050T

safety light curtain transmitter type 2 - XUSLN - height 1050 mm

## Main

Range of product	Preventa Safety detection
Product or component type	Safety light curtains transmitter type 2
Device short name	XUSLN
Product compatibility	XUSLNG5C1050
Design	Compact slim
Product specific application	For hand protection
Minimum object diameter for detection	30 mm
[Sn] nominal sensing distance	0.3...15 m
Height protected	1050 mm
Number of beams	49

## Complementary



Detection system	Transmitter-receiver system
Response time	20 ms
[EAA] effective aperture angle	5 ° at 3 m
Light source	GaAIAs LED, 880 nm
[Us] rated supply voltage	24 V DC (+/- 20 %) against reverse polarity
[Ie] rated operational current	2 A
Current consumption	50 mA
Local signalling	2 LEDs power supply, diagnostic
Electrical connection	1 male connector M12 4 pins
Marking	CE
Material	Front face : acrylic End caps : 30 % fibre glass impregnated nylon Casing : aluminium
Fixing mode	End brackets

## Environment

Standards	IEC 61496-1 IEC 61496-2 (type 2 ESPE) Machinery directive 2006/42/EC EMC 2004/108/EC Work equipment directive 2009/104/EC
Product certifications	CSA TÜV UL
Ambient air temperature for operation	0...55 °C
Ambient air temperature for storage	-25...75 °C
Relative humidity	<= 95 % without condensation
IP degree of protection	IP65
Shock resistance	10 gn for 16 ms conforming to IEC 61496-1
Vibration resistance	0.35 +/- 0.05 mm (f = 10...55 Hz) conforming to IEC 61496-1

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will be Compliant on 3Q2013
Product environmental profile	Available  <a href="#">Download Product Environmental</a>
Product end of life instructions	Available  <a href="#">Download End Of Life Manual</a>